


Overview

HP xw6400 Workstation

HP recommends Microsoft®
Windows® XP Professional



1. Monitor (sold separately)
2. 2004 Standard Keyboard (USB or PS2)
3. Mouse
4. Front IO: 2 USB 2.0, IEEE-1394 (optional), headphone and microphone
5. 3.5" external bay for optional diskette drive or other 3.5" device
6. 2 internal 3.5" bays, 2 external 5.25" bays
7. 2 PCI, 1 PCIe x16 mechanical/x4 electrical, 2 PCIe x8 mechanical/x4 electrical
8. 1 PCI Express x16 Graphics Bus
9. 5 USB 2.0 (rear), 1 USB 2.0 (internal), 1 standard serial port, 1 parallel port, 2 PS/2, 1 RJ-45, audio in/out
10. Dual 64-bit Intel® Xeon® series 5100 processors (availability in 2H 2006)
11. 575 watt power supply

At A Glance

- Choice of operating systems:
 - Microsoft Windows XP Professional
 - Microsoft Windows XP Professional x64 Edition (see <http://www.hp.com/workstations/pws/windowsxp64/> for details)
- Red Hat Enterprise Linux Workstation 3 (32- or 64-bit version as an after market option)
- Red Hat Enterprise Linux Workstation 4 (32- or 64-bit version)
- HP Linux Installer Kit (see <http://www.hp.com/workstations/software/linux/> for details)
- 64-bit dual-core Intel® Xeon® processors (availability in 2H 2006)
- 1066 and 1333 MHz Front Side Bus support
- 4-channel 533 or 667 MHz FB-DIMM memory subsystem
- Up to 16 GB memory capacity
- PCI Express I/O and graphics
- Integrated Broadcom 5752 Gigabit ethernet

Overview

- 4 channels of Serial ATA (SATA) 3 Gb/s natively supported internally; RAID level 0, 1 available on motherboard (HW RAID functionality not supported by Linux)
- High Definition integrated audio with internal speaker
- Pre-loaded Manageability tools
- Energy Star compliance with energy-saving features (Not supported by Linux)
- Protected by HP Services, including a 3 years next business day onsite standard warranty. Terms and conditions vary by country. Certain restrictions and exclusions apply.

Standard Features - Custom Components

Processor and speed –	Dual Core Intel Xeon processor with EM64T
Up to 2 of the following	One or two Dual Core Intel Xeon Processor 5100 Sequence*, 4 MB shared L2 cache per processor
	1.60 GHz/1066
	1.86 GHz/1066
	2.00 GHz/1333
	2.33 GHz/1333
	2.66 GHz/1333
	3.00 GHz/1333
	* Dual Core Intel Xeon Processor 5100 Sequence available 2H 2006

Operating System –	Microsoft Windows XP Professional SP2
One of the following	Microsoft Windows XP Professional x64 Edition (expected availability with Intel Xeon processor 5100 sequence only in 2H 2006)
	Red Hat Enterprise Linux Workstation 3 (32 & 64-bit available as an After Market Option)
	Red Hat Enterprise Linux Workstation 4 (32 & 64-bit available as pre-load and as an After Market Option)
	See http://www.hp.com/workstations/software/linux/
	Click on "Hardware support matrix" under "Related links" for details.

1-3 Hard Disk Drives –		Windows XP	Red Hat Linux
Up to 3 of the following	80 GB 7200 rpm SATA 3 Gb/s drive	32-bit, 64-bit	WS3, WS4
SATA drives, or 3 of the	160 GB 7200 rpm SATA 3 Gb/s NCQ drive	32-bit, 64-bit	WS3, WS4
following SAS drives	250 GB 7200 rpm SATA 3 Gb/s NCQ drive	32-bit, 64-bit	WS3, WS4
	500 GB 7200 rpm SATA 3 Gb/s NCQ drive	32-bit, 64-bit	WS3, WS4
	146 GB 10,000 rpm SAS 3 Gb/s drive	32-bit, 64-bit	WS3, WS4
	73 GB 15,000 rpm SAS 3 Gb/s drive	32-bit, 64-bit	WS3, WS4
	146 GB 15,000 rpm SAS 3 Gb/s drive	32-bit, 64-bit	WS3, WS4

Factory integrated		Windows XP	Red Hat Linux
RAID on motherboard for	RAID 0 Configuration – Striped Array	32-bit, 64-bit	Not supported
SATA drives	RAID 1 Configuration – Mirrored Array	32-bit, 64-bit	Not supported
	RAID 10 Configuration – Striped/Mirrored Array	32-bit, 64-bit	Not supported
	RAID 5 Configuration – Parity Array	32-bit, 64-bit	Not supported
	NOTE: Requires 2 identical hard drives (speeds, capacity, interface)		

Drive controllers		Windows XP	Red Hat Linux
	Integrated SATA 3 Gb/s controller, RAID level 0, 1, 10, 5 supported	32-bit, 64-bit	WS3, WS4 (HW RAID functionality not supported by Linux)

Standard Features - Custom Components

IEEE 1394a FireWire 4-Port PCI Card	32-bit, 64-bit	Not Supported
IEEE 1394b FireWire 4-Port PCI Card	32-bit, 64-bit	Not Supported

Memory – One of the following		Windows XP	Red Hat Linux
512 MB PC2-5300F ECC registered DDR2 667 MHz FB-DIMM (1 x 512 MB)	32-bit, 64-bit	WS3, WS4	
1 GB PC2-5300F ECC registered DDR2 667 MHz FB-DIMM (2 x 512 MB)	32-bit, 64-bit	WS3, WS4	
2 GB PC2-5300F ECC registered DDR2 667 MHz FB-DIMM (4 x 512 MB)		WS3, WS4	
2 GB PC2-5300F ECC registered DDR2 667 MHz FB-DIMM (2 x 1 GB)	32-bit, 64-bit	WS3, WS4	
3 GB PC2-5300F ECC registered DDR2 667 MHz FB-DIMM (2 x 1GB + 2 x 512 MB)	32-bit, 64-bit	WS3, WS4	
4 GB PC2-5300F ECC registered DDR2 667 MHz FB-DIMM (4 x 1 GB)	32-bit, 64-bit	WS3, WS4	

Removable storage		Windows XP	Red Hat Linux
1 .44-MB Diskette Drive	32-bit, 64-bit	WS3, WS4	
48X CD-ROM Drive	32-bit, 64-bit	WS3, WS4	
16X/40X DVD-ROM drive	32-bit, 64-bit	WS3, WS4	
48X/32X/48X/16X Combo CD-RW/DVD-ROM Drive	32-bit, 64-bit	WS3, WS4	
16X DVD+/-RW, Dual-Layer, LightScribe (Windows)	32-bit, 64-bit	WS3, WS4	

2nd Removable storage		Windows XP	Red Hat Linux
16X/40X DVD-ROM drive	32-bit, 64-bit	WS3, WS4	
48X/32X/48X/16X Combo CD-RW/DVD-ROM Drive	32-bit, 64-bit	WS3, WS4	
16X DVD+/-RW, Dual-Layer, LightScribe (Windows)	32-bit, 64-bit	WS3, WS4	

Keyboard – One of the following		Windows XP	Red Hat Linux
PS/2 Standard Keyboard	32-bit, 64-bit	WS3, WS4	
USB Standard Keyboard	32-bit, 64-bit	WS3, WS4	

Mouse – One of the following		Windows XP	Red Hat Linux
PS/2 2-Button Scroll Mouse	32-bit, 64-bit	WS3, WS4	
USB 2-Button Optical Scroll Mouse	32-bit, 64-bit	WS3, WS4	
USB 3-Button Optical Mouse	32-bit, 64-bit	WS3, WS4	

Audio		Windows XP	Red Hat Linux
--------------	--	-------------------	----------------------

Standard Features - Custom Components

Integrated High Definition audio with internal speaker * Via linux drivers on HP support website that are not part of RHEL WS 3	32-bit, 64-bit	WS3, WS4
SoundBlaster X-Fi XtremeMusic audio card	32-bit	Not Supported

NIC	Windows XP	Red Hat Linux
Integrated Broadcom BCM5752 Gigabit LOM,	32-bit, 64-bit	WS3, WS4
Broadcom BCM5751 NetXtreme Gigabit Ethernet Controller (PCI-E)	32-bit, 64-bit	WS3, WS4

Graphics	Windows XP	Red Hat Linux
NVIDIA Quadro NVS 285 PCI Express with NVIDIA TurboCache Technology	32-bit, 64-bit	WS3, WS4
NVIDIA Quadro NVS 440 256 MB PCI Express	32-bit, 64-bit	Not supported
NVIDIA Quadro FX 560 128 MB PCI Express	32-bit, 64-bit	WS3, WS4
ATI FireGL V3300 128 MB PCI Express	32-bit, 64-bit	WS3, WS4
NVIDIA Quadro FX 1500 256 MB PCI Express	32-bit, 64-bit	WS3, WS4
NVIDIA Quadro FX 3500 256 MB PCI Express	32-bit, 64-bit	WS3, WS4
ATI FireGL V7200 256 MB PCI Express	32-bit, 64-bit	WS3, WS4

Software	Windows XP	Red Hat Linux
Optional Symantec Norton AntiVirus (optional)	32-bit, 64-bit	Not supported
Optional Microsoft Office 2003 Basic	32-bit, 64-bit	Not supported
Optional Microsoft Office 2003 Pro	32-bit, 64-bit	Not supported
Optional Microsoft Office 2003 Small Business	32-bit, 64-bit	Not supported
HP Performance Tuning Framework	32-bit, 64-bit	Not supported
HP Client Manager Software v6.0 (expected availability in 2H 2006)	32-bit, 64-bit	Not supported
Optional HP Protect Tools Security Solutions	32-bit, 64-bit	Not supported

Standard Features - Specs

Operating System (choice)	Microsoft Windows XP Professional SP2
	Microsoft Windows XP Professional x64 Edition (expected availability in 2H 2006)
	OR Red Hat Enterprise Linux Workstation 4 64 bit preload (32 bit version included on recovery CD or as after market option)
	OR Red Hat Enterprise Linux Workstation 3 (32 bit and 64 bit) available as an after market option.
	OR HP Installer Kit for Linux (includes drivers for both 32-bit & 64-bit OS versions of RHEL 3 and RHEL 4)
Form factor	Minitower
Color	Carbonite/Alloy metallic
System board form factor	12"x9.8"
Processor	1 or 2 Dual-Core Intel® Xeon® Processor 5100 sequence with EM64T (expected availability in 2H 2006)
CPU FSB	667, 1066, 1333 MHz
Standard L2 cache	2 MB L2 inclusive cache (non ECC) per core, 4 MB total shared cache per processor
Chipset	Intel® 5000X
Memory expansion slots	4 DIMMs
Memory type supported	DDR2 registered ECC FB-DIMMs
Memory speed supported	533 MHz
Maximum memory	16 GB (4 DIMMs slots with 4 GB DIMMS)
Network controller	Integrated Broadcom 5752 Gigabit Ethernet LAN-On-Motherboard
Audio	Integrated high definition digital audio with S/PDIF 6-channel pass-through, stereo microphone, and Yamaha XG Lite Softsynth support If using RHEL WS 3, the audio drivers are not included as part of the standard RHEL WS 3 operating system. Use the ALSA audio drivers included on the HP Driver CD or from the HP support website. See http://www.hp.com/support/linux_hardware_matrix and http://www.hp.com/support/linux_user_manual for details.
PCI slots	2 PCI slots (full-length) 2 PCI Express (x8 mechanically, x4 electrically) 1 PCI Express (x16 mechanically/x4 electrically) 1 PCI Express x16 graphics
Bays	Total Bays = 5
Internal bays	<ul style="list-style-type: none"> Two 3.5 inch HDD bays with acoustic dampening rail assemblies
External bays	<ul style="list-style-type: none"> Two 5.25 inch bays - 203 mm maximum device depth (top bay is limited to 198 mm depth when optional smart cover solenoid lock is installed). Bottom bay can be converted to an internal 3.5 inch 3rd Hard Drive bay using optional bracket One 3.5 inch bay for optional floppy drive
Front I/O	2 USB 2.0, Headphone, Microphone, optional IEEE 1394 NOTE: Although HP Personal Workstations can be ordered with the HP Installer Kit for Linux and an IEEE 1394 card, HP cannot provide customer support for this configuration. Please refer to the Linux Hardware Support Matrix (http://www.hp.com/support/linux_hardware_matrix) for details, and to the Linux User Manual (http://www.hp.com/support/linux_user_manual) for tips on user-enablement of the IEEE 1394 Card.
Internal I/O	1 USB 2.0 header
Rear I/O	5 USB 2.0, 1 standard serial port, 1 parallel port, PS/2 keyboard and mouse, 1 RJ-45 to integrated Gigabit LAN, Audio In, Audio Out, Microphone In
USB keyboard	Optional

Standard Features - Specs

USB mouse	Optional	
PS/2 keyboard	1	
PS/2 mouse	1	
Chassis dimensions (H x W x D)	17.3 x 6.5 X 17.3 in (44.1 x 16.5 x 44.0 cm)	
System weight	Minimum config – 14.60 KG (32.30 lbs) Maximum config – 18.11 KG (39.94 lbs)	
Temperature	Operating	40° to 95° F (5° to 35° C)
	Non-operating	-40° to 140° F (-40° to 60° C)
Humidity	Operating	8% to 85%
	Non-operating	8% to 90%
Maximum altitude (nonpressurized)	Operating	10,000 ft (3,000 m)
	Non-operating	30,000 ft (9,100 m)
Power supply	575W wide-ranging, active Power Factor Correction	
Interfaces supported	4-channel SATA interface (4 serial-ATA connectors each), 2 EIDE interface (2 EIDE connectors) supported for optical drives, USB 2.0, IEEE 1394 (optional)	
Hard drive controller (PCI) Supported	SATA or optional SAS controllers	

After-Market Options

Processors	2 nd dual core Intel Xeon® processor with Hyper-Threading technology, EM64T, and 2 MB of L2 cache per core (4 MB L2 cache in total)	Part Number
	1.60 GHz with 1066 MHz FSB *	EY012AA
	1.86 GHz with 1066 MHz FSB *	EY013AA
	2.00 GHz with 1333 MHz FSB *	EY014AA
	2.33 GHz with 1333 MHz FSB *	EY015AA
	2.66 GHz with 1333 MHz FSB *	EY016AA
	3.00 GHz with 1333 MHz FSB *	EY017AA
	* Expected availability in 2H 2006	

Graphics	Multi display solutions	PCI Express	Windows XP	Red Hat Linux	Part Number
	NVIDIA Quadro NVS 285 (64 MB, VGA & DVI)	X	32-bit, 64-bit	WS3, WS4	EE061AA
	NVIDIA Quadro NVS 440 (256 MB)	X	32-bit, 64-bit	Not supported	PT453A
	NVIDIA Quadro FX 560 (128 MB)	X	32-bit, 64-bit	WS3, WS4	ES354AA
	ATI FireGL V3300 (128 MB)	X	32-bit, 64-bit	WS3, WS4	ES353AA
	NVIDIA Quadro FX 1500 (256 MB)	X	32-bit, 64-bit	WS3, WS4	ES355AA
	NVIDIA Quadro FX 3500 (256 MB)	X	32-bit, 64-bit	WS3, WS4	ES357AA
	ATI FireGL V7200 (256 MB)	X	32-bit, 64-bit	WS3, WS4	ES356AA

Hard drives	SATA Hard Drives	Windows XP	Red Hat Linux	Part Number
	80 GB 7200 rpm SATA 3 Gb/s drive	32-bit, 64-bit	WS3, WS4	DX760A
	160 GB 7200 rpm SATA 3 Gb/s NCQ drive	32-bit, 64-bit	WS3, WS4	PV944A
	250 GB 7200 rpm SATA 3 Gb/s NCQ drive	32-bit, 64-bit	WS3, WS4	EA788AA
	500 GB 7200 rpm SATA 3 Gb/s NCQ drive	32-bit, 64-bit	WS3, WS4	PV943A
	SAS Hard Drives			
	146 GB 10,000 rpm SAS 3 Gb/s drive	32-bit, 64-bit	WS3, WS4	EM173AA
	73 GB 15,000 rpm SAS 3 Gb/s drive	32-bit, 64-bit	WS3, WS4	EA329AA
	146 GB 15,000 rpm SAS 3 Gb/s drive	32-bit, 64-bit	WS3, WS4	EA330AA
	StorCase SATA removable drive enclosure (1 additional HD in a 5.25 inch bay)	NA	NA	EA332AA

Controllers	PCI	PCI-Express	Windows XP	Red Hat Linux	Part Number
Controllers					
IEEE 1394a FireWire 4-Port PCI Card	X		32-bit, 64-bit	Not supported	PA997A
IEEE 1394b FireWire 4-Port PCI Card	X		32-bit, 64-bit	Not supported	EA327AA

After-Market Options

Input/output devices		Windows XP	Red Hat Linux	Part Number
	Keyboards			
	HP PS/2 Standard Keyboard (Carbonite/Silver)	32-bit, 64-bit	WS3, WS4	DT527A
	HP USB Standard Keyboard (Carbonite/Silver)	32-bit, 64-bit	WS3, WS4	DT530A
	HP USB Smartcard Keyboard	32-bit, 64-bit	Not supported	ED707AA
	Pointing Devices			
	HP PS/2 2-Button Scroll Mouse (Carbonite)	32-bit, 64-bit	WS3, WS4	DD440B
	HP USB 2-Button Optical Scroll Mouse (Carbonite/Silver)	32-bit, 64-bit	WS3, WS4	DC172B
	HP USB Optical 3-button mouse	32-bit, 64-bit	WS3, WS4	DY651A
	USB Spaceball 5000	32-bit, 64-bit	Not supported	DV675A
	USB SpaceMouse	32-bit, 64-bit	Not supported	DZ203A
	USB SpacePilot	32-bit, 64-bit	Not supported	EF390AA

Networking	NICs	PCI	PCI-Express	Windows XP	Red Hat Linux	Part Number
	Broadcom BCM5751 NetXtreme Gigabit Ethernet Controller (PCIe)		X	32-bit, 64-bit	WS3, WS4	DZ556A

Memory modules		Windows XP	Red Hat Linux	Part Number
	667 MHz			
	512 MB PC2-5300F ECC registered DDR2 667 MHz FB-DIMM	32-bit, 64-bit	WS3, WS4	EM159AA
	1 GB PC2-5300F ECC registered DDR2 667 MHz FB-DIMM	32-bit, 64-bit	WS3, WS4	EM160AA

Monitors (Supported by all Operating Systems available from HP)	TFT display		Part Number
	HP Flat Panel Monitor TFT LP2465 (24 -inch)		EF224A4
	HP Flat Panel Monitor TFT L2065 (20.1-inch)		EF227A4
	HP Flat Panel Monitor TFT L1955 (19.1-inch)		PD974A5

Optical drives		Windows XP	Red Hat Linux	Part Number
	DVD-ROM Drive			
	16X/40X DVD-ROM w/ +R read	32-bit, 64-bit	WS3, WS4	AA620B
	CD-ROM Drive			
	48X Max CD-ROM Drive (only available as first optical drive)	32-bit, 64-bit	WS3, WS4	DC143B
	Combo Drive			
	48X/32X Combo DVD-ROM/CD-RW Drive	32-bit, 64-bit	WS3, WS4	DE206A

After-Market Options

DVD+/-RW Drive

1.6X DVD+/-RW, Dual-Layer, LightScribe (Windows 2K and XP only)	32-bit	WS3, WS4 (LightScribe functionality not supported)	DZ555A
---	--------	---	--------

Removable storage

	Windows XP	Red Hat Linux	Part Number
512 MB USB 2.0 drive key	32-bit, 64-bit	WS3, WS4	ED516AA
1 GB USB 2.0 drive key	32-bit, 64-bit	WS3, WS4	AG382AA
1.44 MB Internal Floppy Drive	32-bit	WS3, WS4	DY670A

Audio

HP Satellite Stereo Speakers			DE893D
SoundBlaster X-Fi XtremeMusic audio card	32-bit, 64-bit	Not supported	EA326AA

Brackets/stands

xw64 Depth Adjustable Sliding Rail Rack Kit			DY663A
HP Optical Bay HDD Mounting Bracket			DY659A
HP 1U Fixed Rack Shelf			253449-B21
HP 100Kg 1U Sliding Rack Shelf			234672-B21
HP Depth Adjustable Fixed Rail Rack Kit			332558-B21

Other devices

HP Internal USB Port Kit			EM165AA
HP Power Cord Kit			DM293A
"PCI Front Card Guide/Fan Kit			EM163AA

Operating systems


Red Hat Enterprise Linux Workstation 4 (64-bit preload)			EA700AA
---	--	--	---------

Memory

Intel 5000X chipset

PC2-5300F ECC registered DDR2 667 MHz FB-DIMM

The Intel 5000X chipset supports ECC Registered DDR2 667 MHz FB-DIMMs only. The motherboard has 4 DIMM slots. Use only fully buffered, PC2-5300F DIMMs. Match multiple DIMMs by size and type. Use HP memory only.



If only using 1 DIMM, install in socket 1. If using 2 DIMMs, install them in sockets 1 & 3. If using 4 DIMMs, install them in all sockets.

MAXIMUM MEMORY

Supports up to 16 GB of DDR2 FB-DIMM SDRAM.

POSSIBLE MEMORY CONFIGURATIONS


Not all memory configurations possible are represented below.

This chart does not represent all possible memory configurations

DIMM Size	1	2	3	4
256 MB				
512 MB				
512 MB	512 MB			
1 GB				
1 GB	512 MB	512 MB		
1 GB				
2 GB	1 GB	1 GB		
2 GB	512 MB	512 MB	512 MB	512 MB
4 GB	1 GB	1 GB	1 GB	1 GB
8 GB	2 GB	2 GB	2 GB	2 GB
16 GB	4 GB	4 GB	4 GB	4 GB

Storage

Tower configuration



	Quantity Supported	Position Supported	Controller
Convertible minitower			
Optional diskette drive	1	3	IDE
5.25" storage drive bays (position 1 drive bay is limited to 198 mm depth when optional smart cover solenoid lock is installed; position 2 drive bay can be converted to an internal 3.5" 3rd hard drive bay with optional bracket)	2	1, 2	IDE
3.5" storage drive bays with acoustic dampening rail assemblies	2 (3)	5 (and 2, for 3rd drive using optical bay)	SATA or optional SAS Factory Integrated RAID*

SATA and SAS may be mixed only in a Windows configuration and with the inclusion of an optional SAS controller. Here are the rules for mixing hard drives:

- 1) The boot/data drive must be SATA to load before any SAS drive.
- 2) Any size or speeds may be chosen for drives

In non-mixed Microsoft Windows and Linux systems, rules 2 & 3 apply.

Configure-to-order RAID configs must all have the same size/speed hard drives.

Storage

Up to 4 channels of SATA can be supported natively.

* **NOTE:** Factory Integrated RAID 0 Configuration (Striped Array) and RAID 1 Configuration (Mirrored Array) requires 2 hard drives with identical speeds, capacity and interface. Also, HW RAID functionality or factory configured RAID not supported in Linux. For RAID functionality, use SW RAID provided in the Red Hat operating system instead.

Technical Specifications

System board	
Processor architecture	Dual-Core Intel® Xeon® Processor 5100 sequence (expected availability in 2H 2006)
Chipset	Intel® 5000X
Super I/O controller	SMSC SCH5307
System board form factor	9.8"x12.0"
Processor socket	Dual LGA 771
DIMM connectors (FBD DDR2)	4
PCI connectors (5.0V)	2 full length 33 MHz 32-bit
PCI express connectors	1 PCI Express x16 graphics 2 PCI Express (x8 mechanically, x4 electrically) 1 PCI Express (x16 mechanical/x4 electrically)
Flash ROM	Yes
HD integrated audio	Yes
CD-ROM IN (audio)	No
AUX IN (audio)	Yes
Clear CMOS button	Yes
CPU fan headers	Yes
Chassis fan headers	Yes
Front control panel/speaker header	Yes
CMOS battery holder – Lithium	Yes
Hood lock header	No
Hood sensor header	No
Multibay header	No
Integrated SATA RAID	<ul style="list-style-type: none"> • RAID 0, RAID 1, RAID 5 and RAID 10 • Supports one RAID array with 2-4 drives • RAID 0 configuration – striped array • RAID 1 configuration – mirrored array • RAID 5 parity striping • RAID 10 stripe of mirrors <p>NOTE: HW RAID functionality not supported by Linux. Use SW RAID functionality provided in the Red Hat Operating system instead.</p>
Integrated Gigabit Ethernet	Broadcom BCM5752
Wake on LAN	Yes
Integrated Trusted Platform Module	TPM 1.2 expected availability for systems sold at end of 2006/ early 2007
ASF 2.0 (Alert Standard Format)	Yes
SATA connectors	4 ports/connectors

Technical Specifications

IEEE 1394a connectors	No integrated 1394a - optional PCI card required. Cable from Front IO can be plugged into PCI Card. Not supported in Linux
USB 2.0 connectors	8 (5 rear, 2 on header for front, 1 internal)
Power supply headers	Yes
Power switch, power LED & hard drive LED header	Yes
Password clear header	Yes

Cooling solutions	
Power supply fan	92 mm x 25 mm
Processor heatsink fan(s)	80 mm x 15 mm
Rear chassis fan(s)	One 92 mm x 25 mm and one 92 mm x 32 mm

Power supply	
Power supply	575 W watt custom power supply – (Wide Ranging, Active PFC)
Operating voltage range	90 – 269 VAC
Rated voltage range	100 – 240 VAC
Rated line frequency	50/60 Hz
Operating line frequency range	47 – 66 Hz
Rated input current	8A @ 100-120VAC 4 A @ 200-240 VAC
Heat dissipation (configuration and software dependent)	Typical 699 btu/hr (176 kg-cal/hr) Maximum 1962 btu/hr (495 kg-cal/hr)
Power supply fan	92x25 mm variable speed
Energy Star compliant	YES
Blue Angel compliant (<5w in S5 – power off)	N/A
FEMP Standby power compliant @115V (<2W in S5 – power off)	YES
Power consumption in ES mode – Suspend to RAM (S3) (instantly available PC)	< 7 W

ROM Features	Description
ROM based F10 setup and diagnostics	Review and customize BIOS settings
Remote system installation via F12 (PXE) (remote boot from server)	Allows a new or existing system to boot over the network and download software, including the operating system
System/emergency ROM flash recovery with video	Recovers corrupted system BIOS
ROM revision levels	<ul style="list-style-type: none"> Identifies system ROM revision levels and reports in ROM-based F10 setup

Technical Specifications

	Version is stored in an industry standard memory location (SMBIOS) so that management SW applications can use and report this information
System board revision level	<ul style="list-style-type: none"> Allows management SW to read the revision level of the system board Revision level is digitally encoded into the hardware and cannot be modified
Auto setup when new hardware Installed	System automatically detects addition of new hardware
Serial, parallel, USB, audio, network, enable/disable port control	Enable or disables serial, parallel, USB, audio, and network ports
Removable media write/boot control	Prevents ability to boot from removable media on supported devices (and can disable writes to media)
Power-On password	Prevents an unauthorized person from booting up the computer
Setup password	Prevents an unauthorized person from changing the system configuration
Replicated setup	Saves BIOS settings to diskette or USB disk-on-key in human readable file. Repset.exe utility can then replicate these settings on machines being deployed without entering ROM-based F10 setup
Memory change alert (requires HP Client Manager Software)	Alerts management console if memory is removed or changed
Thermal alert (requires HP Client Manager Software)	<p>Monitors the temperature state within the chassis. Three modes:</p> <ul style="list-style-type: none"> NORMAL – normal temperature ranges ALERTED – excessive temperatures are detected. Raises a flag so action can be taken to avoid shutdown or provide for a smoother system shutdown SHUTDOWN – excessive temperatures are encountered. Automatically shuts down the computer without warning before hardware component damage occurs
Master Boot record Security	Detects changes to MBR and optional restoration, useful in protecting from viruses
Remote ROM flash	Provides secure, fail-safe ROM image management from a central network console
Remote Wakeup/shutdown	<ul style="list-style-type: none"> System administrators can power on, restart, and power off a client computer from a remote location. Enables cost-effective power consumption when the administrator needs to distribute software, perform security management, or update the ROM
ACPI (Advanced Configuration and Power Interface)	<ul style="list-style-type: none"> Allows the system to wake from a low power mode Controls system power consumption, making it possible to place individual cards and peripherals in a low-power or powered-off state without affecting other elements of the system <p>Supports ACPI 2.0 for full compatibility with 64-bit operating systems</p>
Keyboard-less operation	The system can be operated without a keyboard
SMBIOS	System Management BIOS 2.3.5, previously known as DMI BIOS, for system management information
Localized ROM setup	Common BIOS image supports configuration (Setup) in 11 languages, with local keyboard mappings
Asset tag	Allows user or MIS to set unique tag string in ROM
Ownership tag	Allows user or MIS to set unique tag string in ROM
Memory scrubbing	Allows memory controller to transparently correct transient ECC errors in the background
Memory remapping	Allows system memory lost to PCI devices to be reclaimed above 4 GB, for use with operating systems that support more than 4 GB (Windows XP 64-bit edition, Linux)
Per-slot control	Allows individual slot configuration (option ROM., latency)
Adaptive cooling	Fan control parameters are set according to detected hardware configuration for optimal acoustics

Technical Specifications

Pre-boot diagnostics	Early (pre-video) critical errors are reported via beeps and blinks on the power LED
Industry Standard	Revision Supported by the BIOS
ACPI	Advanced Configuration and Power Management Interface, Version 2.0
ASF	Alert Standard Format Specification, Version 2.0
ATA (IDE)	AT Attachment 6 with Packet Interface (ATA/ATAPI-6), Revision 3b
ATAPI	ATAPI Removable Media Device BIOS Specification Version 1.0
BBS	BIOS Boot Specification v1.01
BIOS 32-bit Services	Standard BIOS 32-bit Service Directory Proposal
CD Boot	"El Torrito" Bootable CD-ROM Format Specification Version 1.0
EDD	<ul style="list-style-type: none"> Enhanced Disk Drive Specification Version 1.1 BIOS Enhanced Disk Drive Specification Version 3.0
EHCI	Enhanced Host Controller Interface for Universal Serial Bus, Revision 1.0
PCI	<ul style="list-style-type: none"> PCI Local Bus Specification, Revision 2.3 PCI Power Management Specification, Revision 1.1 PCI Firmware Specification, Revision 3.0, Draft .7
PCI Express	PCI Express Base Specification, Revision 1.0a
PMM	POST Memory Manager Specification, Version 1.01
SATA	<ul style="list-style-type: none"> Serial ATA Specification, Revision 1.0a Serial ATA 3 Gb/s: Extensions to Serial ATA 1.5 Gb/s, Revision 1.0
SAS	SAS specification 1.1
SMBIOS	System Management BIOS Reference Specification, Version 2.4
SPD	PC SDRAM Serial Presence Detect (SPD) Specification, Revision 1.2B
UHCI	Universal Host Controller Interface Design Guide, Revision 1.1
USB 1.1	Universal Serial Bus Revision 1.1 Specification
USB 2.0	Universal Serial Bus Revision 2.0 Specification

Other deployment & management features	
HP Client Management Solutions (Windows XP only)	<p>HP Client Management Solutions help simplify management of Workstations and significantly reduce total ownership costs. These solutions share a common design and are highly integrated.</p> <p>HP Client Manager Software is included free with all HP business PCs and Workstations. It enables central tracking, monitoring, and management of the hardware aspects of HP client systems:</p> <ul style="list-style-type: none"> Get valuable hardware information such as CPU, memory, video, and security settings Monitor system health to fix problems before they occur Install drivers and BIOS updates without visiting each PC Remotely configure BIOS and security settings Automate processes to quickly resolve hardware problems <p>Additional solutions (fee-based) are available to address Workstation management challenges through the entire IT lifecycle including:</p> <ul style="list-style-type: none"> Inventory assessment Software license compliance Personality migration Software image deployment Software distribution Asset management Client backup and recovery

Technical Specifications

	<ul style="list-style-type: none"> • Problem resolution <p>Visit http://www.hp.com/go/clientmanager for more information, to download HP Client Manager Software.</p>
HP ProtectTools (Windows XP only)	<p>HP ProtectTools Security Manager can be configured to prevent unauthorized access using Smart Cards, TPM Embedded security chips, USB tokens and other security technologies. HP ProtectTools Security Manager is completely customizable, which gives customers the flexibility to choose the level of security that best meets their needs.</p> <ul style="list-style-type: none"> • Smart Card security for HP ProtectTools <ul style="list-style-type: none"> ◦ Initialization and configuration of the Smart Card ◦ Manage Smart Card accounts and security settings • Embedded Security for HP ProtectTools <ul style="list-style-type: none"> ◦ TPM Embedded Security Chip configuration and management • Credential Manager for HP ProtectTools <ul style="list-style-type: none"> ◦ Multifactor Windows Authentication ◦ Single sign-on • BIOS configuration for HP ProtectTools <ul style="list-style-type: none"> ◦ BIOS configuration and security settings from within the HP ProtectTools Security Manager console <p>Visit http://h18004.www1.hp.com/products/security/ for more information on HP ProtectTools.</p>
System Software Manager (free - Windows XP only)	<p>A free utility that detects and updates BIOS, device drivers, and management agent versions on your networked PCs and workstations</p>
Replicated setup	<p>Saves BIOS settings to diskette or USB disk-on-key in human readable file. Repset.exe utility can then replicate these settings on machines being deployed without entering ROM-based F10 setup</p>
Software restore CD	<p>Restores computer to its original factory shipping image; No recovery CDs will ship with Linux – an ISO image will be available on an HD partition.</p>
Asset tag	<ul style="list-style-type: none"> • Repository for storing company-specific property asset numbers for easy tracking • Initially set equal to the system serial number • Stored in a protected section of non-volatile memory that can be accessed and modified with the F10 Setup program
DIMM serial presence detect	<p>Detects whether or not memory DIMMs are present and their type</p>
Hard drive serial number, model, and manufacturer	<p>Hard drive manufacturer, model, and serial number is stored in the hard drive firmware and reported in ROM-based F10 setup</p>
Memory Change Alert (Requires HP Client Manager Software – Windows XP only)	<p>Alerts management console if memory is removed or changed</p>
Ownership tag	<p>A user-defined string stored in non-volatile memory that is displayed in the BIOS splash screen</p>
Protocol-level Integrity Monitoring (CRC checking)	<p>A feature of SATA and SAS, Cyclic Redundancy Checking provides command, data and message transfer verification and proactive notification of problems with recommendations for enhancing system performance. It detects all the following errors' types:</p> <ul style="list-style-type: none"> • single bit errors • double bit errors • an odd number of errors • error bursts up to 32-bits long
Drive self tests (DPS)	<ul style="list-style-type: none"> • Drive Protection System • A diagnostic hard drive self test. It scans critical physical components and every sector of the

Technical Specifications

	<p>hard drive for physical faults and then reports any faults to the user.</p> <ul style="list-style-type: none"> Running independently of the operating system, it can be accessed through the computer's setup procedure. It produces an evaluation on whether the hard drive is the source of the problem and needs to be replaced. <p>The system expands on the Self-Monitoring, Analysis, and Reporting Technology (SMART), a continuously running systems diagnostic that alerts the user to certain types of failures. DPS Access through F10 Setup during Boot (F10 diagnostic access not available with SCSI drives)</p>
SMART technology (Self-monitoring, analysis and reporting technology – Windows XP only)	<p>Allows hard drives to monitor their own health and to raise flags if imminent failures were predicted. Predicts failures before they occur. Tracks fault prediction and failure indication parameters such as re-allocated sector count, spin retry count, calibration retry count.</p> <p>By avoiding actual hard drive failures, SMART hard drives act as "insurance" against unplanned user downtime and potential data loss from hard drive failure.</p> <p>SMART I – Drive Failure Prediction SMART II – Off-Line Data Collection SMART III – Off-Line Read Scanning with Defect Reallocation</p>
Serviceability Features of System	
Access panel	Tool-less, one-handed
Optical drives	Tool-less
Floppy drive	Tool-less
Hard drives	Tool-less
Expansion cards	Tool-less
Chassis fan removal	Tool-less
Green user touch points	Yes, on tool-free internal chassis mechanisms
Color-coordinated cables and connectors	Yes
Memory	Tool-less
CPUs	Requires T15 Torx driver, can be upgraded without removing any internal components except processor heat sink.
Power supply diagnostic LED	Yes, dual function: AC OK & power OK
Power button	Yes, ACPI multi-function
Power LED	Yes, dual color LED indicates normal operation and faults.
Hard drive activity LED	Yes
Internal speaker	Yes, used for pre-boot diagnostic beep codes
Dual color power and HD LED on front panel (Indicates normal Operations and fault Conditions)	green – normal red – fault
System/emergency ROM flash recovery with video	Recovers corrupted system BIOS.
Configuration record SW	Yes
Over-temp warning on screen (Requires IM	Yes

Technical Specifications

Agents)	
OS CD (Restore OS CD)	Restores computer to its original factory shipping image; No recovery CDs will ship with Linux – an ISO image will be available on an HD partition.
Restore CD	Restores the computer to its original factory shipping image
Flash ROM	Yes
3.3V Aux Power LED on system PCA	No
Dual Function 5V Aux Power LED (ON)/PS_ON LED (OFF) on system PCA	No
Diagnostic power switch LED on board	No
Clear password jumper	Yes
Clear CMOS button	Yes
CMOS Battery Holder for easy replacement	Yes
Processor ZIF Socket for easy upgrade	Yes
DIMM connectors for easy upgrade	Yes
NIC LEDs (integrated) (Green & Amber)	Used to determine NIC status
ASF 2.0 support (Alert Standard Format)	Industry-standard specification for network alerting in operating system-absent environments
Dual function front power switch	Also acts as a reset switch when held for 4 seconds
Service and Support	<p>On-site Warranty and Service (Note 1): This three-year, limited warranty and service offering delivers three years of on-site, next business-day (Note 2) service for parts and labor and includes free telephone support (Note 3) 8am – 5pm. Global coverage (Note 2) ensures that any product purchased in one country and transferred to another, non-restricted country will remain fully covered under the original warranty and service offering.</p> <p>NOTE 1: Terms and conditions may vary by country. Certain restrictions and exclusions apply.</p> <p>NOTE 2: On-site service may be provided pursuant to a service contract between HP and an authorized HP third-party provider, and is not available in certain countries. Global service response times are based on commercially reasonable best effort and may vary by country.</p> <p>NOTE 3: Technical telephone support applies only to HP-configured, HP and HP-qualified, third-party hardware and software. Toll-free calling and 24 x 7 support may not be available in some countries.</p>

Eco-Label Certifications & declarations

This product has received or is in the process of being certified to the following approvals and may be labeled with one or more of these marks:

- US Energy Star (Not in Linux)
- US Federal Energy Management Program (FEMP)
- China Energy Conservation Program
- IT ECO declaration
- Japan PC Green label*

*NOTE: This product conforms to the examination standards (2003 version) under JEITA's 'PC Green

Technical Specifications

Label System.1

Energy Consumption and noise emissions

System Configuration The configuration used for the Energy Consumption and Declared Noise Emissions data for the Convertible Mini tower Desktop model is based on a "Typically Configured Desktop"

Processor Info	2x2 GHz
Memory Info	4x1 GB 667 MHz
Graphics Info	FX 1500
Disks/Optical/Floppy	2x 80 GB SATA / 1 Optical / 1 Floppy

Energy Consumption

	115 VAC		230 VAC		100 VAC	
	LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled
Windows Idle (S0)	180 W		176 W		180 W	
Windows Busy (S0)	205 W		200 W		203 W	
Sleep (S3)	4.1 W	4.3 W	4.8 W	4.1 W	4.3 W	4.8 W
Off (S5)	2.4 W	2.0 W	3.0 W	2.4 W	2.0 W	3.0 W

Heat Dissipation**

	115 VAC		230 VAC		100 VAC	
	LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled
Windows Idle (S0)	614 BTU/hr		501 BTU/hr		614 BTU/hr	
Windows Busy (S0)	700 BTU/hr		683 BTU/hr		691 BTU/hr	
Sleep (S3)	14 BTU/hr	15 BTU/hr	16 BTU/hr	14 BTU/hr	15 BTU/hr	16 BTU/hr
Off (S5)	8.2 BTU/hr	6.8 BTU/hr	10 BTU/hr	8.2 BTU/hr	6.8 BTU/hr	10 BTU/hr

NOTES:

* Energy Star low energy mode

** Heat dissipation is calculated based on the measured watts, assuming the service level is attained for one hour.

This product is in compliance with US executive order 13221, WOL (wake on LAN) disabled.

Declared Noise Emissions

(in accordance with ISO 7779 and ISO 9296)

	Sound Power (LWad, bels)	Deskside Sound Pressure (LpAm, decibels)
Idle	TBD	TBD
Fixed Disk (random writes)	TBD	TBD
Optical Drive (sequential reads)	TBD	TBD

Longevity and Upgrading

This product is designed to be upgraded, possibly extending its useful life by several years. Spare parts are available throughout the warranty period and for up to 5 years after the end of production. Upgradeability features contained in the product include:

- Intel LGA775 processor socket
- 8 USB ports
- 2 PCI slots and 4 PCI Express slots
- 5 storage bays
- 4 memory slots

Technical Specifications

Batteries

This product complies with ISO standards:

- EU Directive 91/ 157/ EEC
- EU Directive 93/ 86/ EEC
- EU Directive 98/ 101/ EEC

Batteries used in the product do not contain:

- Mercury greater the 5ppm by weight
- Cadmium greater than 10ppm by weight
- Lead greater than 4000ppm by weight.

Battery size: CR2032 (coin cell)

Battery type: Lithium

Additional Information

- This product is in compliance with the Restrictions of Hazardous Substances (RoHS) directive – 2002/95/EC.
- This HP product is designed to comply with the Waste Electrical and Electronic Equipment (WEEE) Directive – 2002/96/EC.
- Plastics parts weighing over 25 grams used in the product are marked per ISO 11469 and ISO1043.
- This product contains 0% recycled materials (by wt.)
- This product is >90% recycle-able when properly disposed of at end of life.

Packaging Materials

External	Cardboard carton and insert	2.70 kg
Internal	LDPE Foam	0.35 kg

Material Usage

This product does not contain any of the following substances in excess of regulatory limits (refer to the HP General Specification for the

Environment at http://www.hp.com/hpinfo/globalcitizenship/environment/supplychain/gen_specifications.html):

- Asbestos
- Certain Azo Colorants
- Certain Brominated Flame Retardants – may not be used as flame retardants in plastics
- Cadmium
- Chlorinated Hydrocarbons
- Chlorinated Paraffins
- Formaldehyde
- Halogenated Diphenyl Methanes
- Lead carbonates and sulfates
- Lead and Lead compounds
- Mercuric Oxide Batteries
- Nickel – finishes must not be used on the external surface designed to be frequently handled or carried by the user.
- Ozone Depleting Substances
- Polybrominated Biphenyls (PBBs)
- Polybrominated Diphenyl Ethers (PBDEs)
- Polybrominated Biphenyl Oxides (PBBOs)
- Polychlorinated Biphenyl (PCB)
- Polychlorinated Terphenyls (PCT)
- Polyvinyl Chloride (PVC) – except for wires and cables, and certain retail packaging has been voluntarily removed from most applications.
- Radioactive Substances
- Tributyl Tin (TBT), Triphenyl Tin (TPT), Tributyl Tin Oxide (TBTO)

Packaging

HP follows these guidelines to decrease the environmental impact of product packaging:

Technical Specifications

- Eliminate the use of heavy metals such as lead, chromium, mercury and cadmium in packaging materials.
- Eliminate the use of ozone-depleting substances (ODS) in packaging materials.
- Design packaging materials for ease of disassembly.
- Maximize the use of post-consumer recycled content materials in packaging materials.
- Use readily recyclable packaging materials such as paper and corrugated materials.
- Reduce size and weight of packages to improve transportation fuel efficiency.
- Plastic packaging materials are marked according to ISO 11469 and DIN 6120 standards.

End-of-life Management and Recycling

Hewlett-Packard offers end-of-life HP product return and recycling programs in many geographic areas. To recycle your product, please go to: <http://www.hp.com/recycle> or contact your nearest HP sales office. Products returned to HP will be recycled, recovered or disposed of in a responsible manner.

Hewlett-Packard Corporate Environmental Information

For more information about HP's commitment to the environment:

[link to new HP white paper now in progress]

Global Citizenship Report

<http://www.hp.com/hpinfo/globalcitizenship/gcreport/index.html>

Eco-label certifications

<http://www.hp.com/hpinfo/globalcitizenship/environment/productdesign/ecolabels.html>

ISO 14001 certificates:

<http://www.hp.com/hpinfo/globalcitizenship/environment/operations/envmanagement.html>

Technical Specifications – Audio

<p>High Definition Integrated Type Realtek ALC262 Audio</p>	<p>Integrated</p>
<p>High Definition codec</p>	<p>Yes</p>
<p>SPDIF</p>	<p>No</p>
<p>External audio jacks</p>	<p>One front stereo analog microphone-in One front stereo headphone-out One rear line-in One rear line-out One rear stereo analog microphone-in</p>
<p>Internal audio connectors</p>	<p>AUX-IN line-level analog input</p>
<p>Retasking</p>	<p>NOTE: All external audio ports are retaskable as Line-In, Line-Out, Microphone-In, or Headphone-Out</p>
<p>Sampling</p>	<p>44.1 kHz/48 kHz/96 kHz/192 kHz (output only)</p>
<p>Wavetable syntheses (software)</p>	<p>Yes – Uses OS soft wavetable</p>
<p>Digital audio</p>	<p>Yes</p>
<p>Analog audio</p>	<p>Yes</p>
<p>Number of channels on Line-Out (mono/stereo)</p>	<p>Two independent stereo outputs (Left & Right channels)</p>
<p>Internal audio speaker power rating</p>	<p>1.5 W</p>
<p>Internal speaker</p>	<p>Yes</p>
<p>Microphone features</p>	<p>Stereo Microphone supporting: Acoustic echo cancellation Noise suppression Beam forming</p>

<p>SoundBlaster X-Fi XtremeMusic audio card Windows XP Only</p>	<p>Audio Quality</p>	<p>Total Harmonic Distortion + Noise at 1 kHz (20kHz Low-pass filter) = 0.004%</p>
	<p>Signal to Noise Ratio (SNR)</p>	<p>Signal-to-Noise Ratio (20kHz Low-pass filter, A-Weighted) Stereo Output: 109dB Front and Rear Channels: 109dB Center, Subwoofer and Side Channels: 109dB</p>
	<p>Sound Conversion</p>	<p>24-bit Analog-to-Digital conversion of analog inputs at 96kHz sample rate 24-bit Digital-to-Analog conversion of digital sources at 96kHz to analog 7.1 speaker output 24-bit Digital-to-Analog conversion of stereo digital sources at 192kHz to stereo output</p>

Technical Specifications – Audio

Recording/ Sampling Rate	16-bit to 24-bit recording sampling rates: 8, 11.025, 16, 22.05, 24, 32, 44.1, 48 and 96 kHz	
ASIO 2.0 support	16-bit/44.1kHz, 16-bit/48kHz, 24-bit/44.1kHz 24-bit/48kHz and 24-bit/96kHz with direct monitoring	
Enhanced SoundFont support	Up to 24-bit resolution	
DACs	24-bit/96kHz	
Voice Support	24-bit/192kHz	
Max. Channels in 3D Positional Audio	128 voices	
EAX® ADVANCED HD™ 5.0 support	7.1	
Connectors	Yes including EAX® MacroFX™, EAX® PurePath™ and Environment FlexiFX™	
	FlexiJack (Performing a 3-in-1 function, Digital In / Line In / Microphone) via 3.50 mm minijack	
	Line level out (Front / Rear / Center / Subwoofer / Rear Center) via 3.50 mm minijacks	
	AUX_IN line-level analog input via 4-pin Molex connector on card	
	One AD_Link (26 pin) connector for linking to the X-Fi I/O Console (upgrade option)	
Dimensions	7.25" x5" x .9" (x x)	
Additional product features	Movies	THX Certification Dolby Digital EX 6.1 Playback DTS-ES 6.1 Playback
	Music	X-Fi 24-bit Crystalizer CMSS-3D SuperRipÔ
	Audio Creation	Pristine audio playback quality with a near transparent SRC engine Up to eight 24 bit hardware effects ASIO recording with latency as low as one millisecond 24-bit SoundFont® sampling 3D MIDI
Minimum system requirements	System RAM	256MB
	Hard disk	600MB free space Available PCI 2.1 slot for the audio card CD-ROM/CD-RW or CD/DVD-ROM required for software installation
	Operating System	Microsoft® Windows® XP Service Pack 2 (SP2)

Technical Specifications – Peripherals

Integrated Broadcom BCM5752 LAN-on-Motherboard	Connector	RJ-45	
	Controller	Intel 82540EM Gigabit Controller	
	Memory	Integrated 96Kb frame buffer memory	
	Data rates supported	10/100/1000 Mbps	
	Compliance	IEEE 802.1A, 802.1P, 802.1P, 802.1Q, 802.2, 802.3, 802.3AB and 802.3u compliant, 802.3x flow control	
	Bus architecture	PCI 2.2	
	Data transfer mode	Bus-master DMA	
	Hardware certifications	FCC, B, CE, TUV- cTUVus Mark Canada and United States, TUV- GS Mark for European Union	
	Power requirement	1.48 watts @ +3.3V AUX supply with 5V tolerance	
	Boot ROM support	Yes	
	Network transfer rate	10BASE-T (half-duplex)	10 Mbps
		10BASE-T (full-duplex)	20 Mbps
		100BASE-TX (half-duplex)	100 Mbps
		100BASE-TX (full-duplex)	200 Mbps
1000BASE-T		1000 Mbps	
Operating system driver support	Microsoft Windows XP, Red Hat Enterprise Linux WS 3, Red Hat Enterprise Linux WS 4		
Management capabilities	ACPI, WOL and DMI 2.0, PXE 2.0, WfM 2.0, Intel PROset II utility		

Broadcom BCM5751 NetXtreme Gigabit Ethernet Controller (PCIe)	Connector	RJ-45	
	Controller	Broadcom 5751 PCIE 1.0a LAN Controller	
	Memory	Integrated 96Kb frame buffer memory	
	Data rates supported	10/100/1000 Mbps	
	Compliance	IEEE 802.3, 802.3AB and 802.3u compliant, 802.3x flow control	
	Bus architecture	PCIe 1.0a	
	Data path width	X1	
	Data path speed	2.5Gbit per sec per direction transfer rate	
	Data transfer mode	Bus-master DMA	
	Hardware certifications	FCC class B, NRTL Mark Canada and United States, C-Tick for Australia, BSMI for Taiwan, VCCI for Japan, MIC for Korea, GOST for Russia	
	Power requirement	3.1 watts @ +3.3V AUX supply	
	Boot ROM support	Yes	
	Network transfer rate	10BASE-T (half-duplex)	10 Mbps
		10BASE-T (full-duplex)	20 Mbps
100BASE-TX (half-duplex)		100 Mbps	
100BASE-TX (full-duplex)		200 Mbps	
1000BASE-T		1000 Mbps	

Technical Specifications – Peripherals

Environmental	Operating temperature	32° to 131° F (0° to 55° C)
	Operating humidity	85% at 131° F (55° C)
Dimensions		4.4 x 2.2 x 0.08 in (11.2 x 5.5 x .2 cm)
Operating system driver support		Microsoft Windows XP, Red Hat Enterprise Linux WS 3, Red Hat Enterprise Linux WS 4
Management capabilities		WOL, PXE , Remote cable management
Alerting		ASF 2.0
Kit contents		Broadcom 5751, CD, Broadcom NetXtreme Gigabit Ethernet PCI NIC, drivers, quick install guide, product warranty statement

SATA 3Gb/s hard drives	80 GB	Capacity	80,026,361,856 bytes	
		Height	1 in (2.54 cm) or less	
		Width	Media diameter: 3.5 in (8.89 cm)	
			Physical size: 4 in (10.2 cm)	
			Interface	
		Synchronous Transfer Rate (Maximum)	Up to 300 MB/s	
	Cache	8 MB		
	Seek Time (typical reads, includes controller overhead, including settling)	Single Track	0.9 ms	
		Average	11.0 ms	
		Full-Stroke	18 ms	
	Rotational Speed	7,200 rpm		
	Logical Blocks	156,301,488		
	Operating Temperature	41° to 131° F (5° to 55° C)		
160 GB	160 GB	Capacity	160,041,885,696 bytes	
		Height	1 in (2.54 cm)	
		Width	Media diameter: 3.5 in (8.89 cm)	
			Physical size: 4 in (10.2 cm)	
			Interface	
		Synchronous Transfer Rate (Maximum)	300 MB/s	
	Cache	8 MB		
	Seek Time (typical reads, includes controller overhead, including settling)	Single Track	0.9 ms	
		Average	11.0 ms	
		Full-Stroke	18 ms	
	Rotational Speed	7,200 rpm		
	Logical Blocks	312,581,808		
	Operating Temperature	41° to 131° F (5° to 55° C)		
250 GB	250 GB	Capacity	250,059,350,016 bytes	

Technical Specifications – Peripherals

Height	1 in (2.54 cm)
Width	Media diameter: 3.5 in (8.89 cm) Physical size: 4 in (10.2 cm)
Interface	Serial ATA (3.0 Gb/s), Native Command Queuing enabled
Synchronous Transfer Rate (Maximum)	300 MB/s
Cache	16 MB
Seek Time (typical reads, includes controller overhead, including settling)	Single Track 1.0 ms Average 11.0 ms Full-Stroke 18 ms
Rotational Speed	7,200 rpm
Logical Blocks	488,397,168
Operating Temperature	41° to 131° F (5° to 55° C)

500 GB

Capacity	500,107,862,016 bytes
Height	1 in (2.54 cm)
Width	Media diameter: 3.5 in (8.89 cm) Physical size: 4 in (10.2 cm)
Interface	Serial ATA (3.0 Gb/s), Native Command Queuing enabled
Synchronous Transfer Rate (Maximum)	300 MB/s
Cache	16 MB
Seek Time (typical reads, includes controller overhead, including settling)	Single Track 1.3 ms Average 20.0 ms Full-Stroke 30 ms
Rotational Speed	7,200 rpm
Logical Blocks	976,773,168
Operating Temperature	41° to 131° F (5° to 55° C)

Serial Attached SCSI (SAS) hard drives

146 GB
(10K rpm)

Capacity	146,815,737,856 bytes
Height	1.0 in (25.4mm)
Width	4.0 in (101.6mm)
Interface	SAS
Synchronous Transfer Rate (Maximum)	3.0 Gb/s
Buffer	8 MB
Seek time (typical reads, including settling)	Single track .3 ms Average <4.5 ms Full-stroke <11.0 ms
Rotational Speed	10,000 rpm
Logical Blocks	286,749,488 – 512 byte blocks

Technical Specifications – Peripherals

	Operating Temperature	50° to 95° F (10° to 35° C)	
72 GB (15K rpm)	Capacity	73,407,856,856 bytes	
	Height	1.0 in (25.4mm)	
	Width	4.0 in (101.6mm)	
	Interface	SAS	
	Synchronous Transfer Rate (Maximum)	3.0 Gb/s	
	Buffer	8 MB	
	Seek Time (typical reads, including settling)	Single Track	0.27 ms
		Average	3.5 ms
		Full-Stroke	7.4 ms
	Rotational Speed	15,000 rpm	
	Logical Blocks	143,374,738 – 512 byte blocks	
	Operating Temperature	50° to 95° F (10° to 35° C)	
	146 GB (15K rpm)	Capacity	146,815,737,856 bytes
Height		1.0 in (25.4mm)	
Width		4.0 in (101.6mm)	
Interface		SAS	
Synchronous Transfer Rate (Maximum)		3.0 Gb/s	
Buffer		8 Mbytes	
Seek Time (typical reads, including settling)		Single Track	0.27 ms
		Average	3.5 ms
		Full-Stroke	7.4 ms
Rotational Speed		15,000 rpm	
Logical Blocks		286,749,488 – 512 byte blocks	
Operating Temperature		50° to 95° F (10° to 35° C)	

HP IEEE 1394aFireWire 4-Port PCI Card (Windows XP Only)	Device Interface Protocol	IEEE-1394a	
	Host Bus Burst Data Rate	400 Mbps	
	Devices Supported	IEEE-1394 compliant devices	
	Bus Interface	PCI	
	Physical	PCI card with brackets for low profile and full height PCI slots.	
	Environmental	Operating temperature	50° to 131° F (10° to 55° C)
		Non-operating temperature	-22° to 140° F (-30° to 60° C)

Technical Specifications – Peripherals

	Relative humidity	20% to 80%
Ports		Two IEEE1394 6-Pin Connector (Rear)
Connectors		One 10-Pin (9 Contacts) Custom Connector (Internal)
Minimum System Requirements		Microsoft Windows XP Professional, Windows XP Home, not supported on Linux Pentium II 266 or above 128-MB RAM 1-GB Hard Drive CD-ROM drive Built-in sound system Available PCI slot
Regulatory Agency Approval		FCC Part 15B, cULus 60950, CE Mark EN55022B(1995)/EN55024-1998 STD, Taiwan BSMI CNS13438, Korea MIC

HP IEEE 1394b FireWire 4-Port PCI Card (Windows XP Only)	Device Interface Protocol	IEEE-1394a	
	Host Bus Burst Data Rate	400 Mbps	
	Devices Supported	IEEE-1394 compliant devices	
	Bus Interface	PCI	
	Physical	PCI card with brackets for low profile and full height PCI slots.	
	Environmental	Operating temperature	50° to 131° F (10° to 55° C)
		Non-operating temperature	-22° to 140° F (-30° to 60° C)
		Relative humidity	20% to 80%
	Ports		Two IEEE1394 6-Pin Connector (Rear)
	Connectors		One 10-Pin (9 Contacts) Custom Connector (Internal)
	Minimum System Requirements		Microsoft Windows XP Professional, Windows XP Home, not supported on Linux Pentium II 266 or above 128-MB RAM 1-GB Hard Drive CD-ROM drive Built-in sound system Available PCI slot
	Regulatory Agency Approval		FCC Part 15B, cULus 60950, CE Mark EN55022B(1995)/EN55024-1998 STD, Taiwan BSMI CNS13438, Korea MIC

USB 2.0 Disk on Key	Dimensions (HxWxD)	0.9 x 0.7 x 3.9 in (2.3 x 1.8 x 9.8 cm)
---------------------	---------------------------	---

Technical Specifications – Peripherals

Weight	0.05 lb (0.02 kg)
USB Specification	2.0
Transfer Rate	Read-1023 KB/Sec; Write-850 KB/Sec
Storage Media	Solid state flash memory, no moving parts
Power Supply	USB Bus-powered, no external power required
Capacity	512 MB or 1 GB

HP StorCase Removable Enclosure	Physical characteristics	Dimensions of carrier (H x W x D)	1.07 x 4.34 x 7.54 inches (27.2 x 110.2 x 191.5 mm)	
		Weight of carrier	1 lbs (0.45 kg)	
		Dimensions of receiving frame (H x W x D)	1.62 x 5.75 x 7.88 inches (41.1 x 146.1 x 200.2 mm)	
		Weight of receiving frame	N/A	
		Dimensions of receiving frame - including front bezel (H x W x D)	1.62 x 5.81 x 8.08 inches (41.1 x 147.6 x 205.2 mm)	
		Weight of receiving frame - including front bezel	2 lbs (0.91 kg) (1)	
		Features	Allows you to mount a low-profile (up to 1 inch high) 3.5 inch form factor drive into any half-height, 5.25 inch peripheral bay Supports Serial Attached SCSI (SAS) or Serial ATA 3 Gb/s drives	
			<ul style="list-style-type: none"> • Drive carrier key lock • Drive spin/power up/down button • Power, spin, and fan failure indicator • Drive activity indicator • Soft Start circuitry & anti-static device protection • Cable-less drive connector • 50K mating connector • Cooling fan 	
		Electrical	Input	+5V 9mA / +12V 20 μ A
		Chassis reliability/maintainability	MTBF (at 30° F)	600,000 hours
MTTR	5 minutes			
Environmental	Operating ambient temperature	0° to 50° C		
	Storage ambient temperature	-40° to 70° C		
	Operating relative humidity (2)	5% to 95% 1000 to 10,000 ft		
	Storage relative humidity (2)	50% to 95% -1000 to 40,000 ft		

Technical Specifications – Peripherals

Operating altitude	-305m to 3048m
Storage altitude	-305m to 12195m
Operating shock (3)	60g
Storage shock (3)	30
	1) With carrier removed
	2) Non-condensing with maximum gradient of 10% per hour
	3) Half-sine wave shock pulses at 2ms

PS/2 OR USB '04 Standard Keyboard	Physical characteristics	Keys	104, 105, 106, 107, 109 layout (depending upon country)
		Dimensions (L x W x H)	18.0 x 6.4 x 0.98 in (45.8 x 16.3 x 2.5 cm)
	Electrical	Weight	2 lb (0.9 kg) minimum
		Operating voltage	+ 5VDC ± 5%
		Power consumption	50-mA maximum (with three LEDs ON)
		ESD	CE level 4, 15-kV air discharge
	Mechanical	EMI - RFI	Conforms to FCC rules for a Class B computing device
		Microsoft PC 99 - 2001	Functionally compliant
		Languages	38 available
		Keycaps	Low-profile design
		Switch actuation	55-g nominal peak force with tactile feedback
		Switch life	20 million keystrokes (using Hasco modified tester)
		Switch type	Contamination-resistant switch membrane
		Key-leveling mechanisms	For all double-wide and greater-length keys
		Cable length	6 ft (1.8 m)
		Microsoft PC 99 - 2001	Mechanically compliant
	Environmental	Acoustics	43-dBA maximum sound pressure level
		Operating temperature	50° to 122° F (10° to 50° C)
		Non-operating temperature	-22° to 140° F (-30° to 60° C)
		Operating humidity	10% to 90% (non-condensing at ambient)
		Non-operating humidity	20% to 80% (non-condensing at ambient)
		Operating shock	40 g, six surfaces
		Non-operating shock	80 g, six surfaces
		Operating vibration	2-g peak acceleration
		Non-operating vibration	4-g peak acceleration
		Drop (out of box)	26 in (66 cm) on carpet, six-drop sequence
	Drop (in box)	42 in (107 cm) on concrete, 16-drop sequence	

Technical Specifications – Peripherals

Operating system support	Microsoft XP Professional, and XP Professional x64 Edition, Red Hat Enterprise Linux WS 3, Red Hat Enterprise Linux WS 4
Approvals	UL, CSA, FCC, CE Mark, TUV, TUV GS, VCCI, BSMI, C-Tick, MIC
Ergonomic compliance	ANSI HFS 100, ISO 9241-4, and TUVGS
Kit contents	Keyboard, keyboard software media, installation guide, warranty card, safety and comfort

HP 2-Button Scroll Mouse (PS/2)	Scroll Wheel	8 mm		
	Maximum Rotation Speed	30 mm/s		
	Switch Type	Light force micro-switch		
	Switch Life	1 million operations		
	Mechanical Life	Minimum 200,000 revolutions		
	Environmental	Operating Temperature	50° to 122° F (10° to 50° C)	
		Non-operating Temperature	-22° to 140° F (-30° to 60° C)	
		Operating Humidity	10% to 90% (non condensing at ambient)	
		Non-operating Humidity	20% to 80% (non condensing at ambient)	
		Operating Shock	40 g, 6 surfaces	
		Non-operating Shock	80 g, 6 surfaces	
		Operating Vibration	2 g peak acceleration	
		Non-operating Vibration	4 g peak acceleration	
		Mechanical	Resolution	400 ± 20% DPI
			Tracking Speed	10 in/s maximum
	Acceleration		100 in/s	
	Switch Actuation		85 g nominal peak force	
	Switch Life		1,000,000 operations (using Hasco modified tester)	
	Cable Length		2 m	
Regulatory Approvals	PC98-99	Mechanically compliant		
		UL, CSA, FCC, CE Mark, TUV, TUV GS, VCCI, BCIQ, C-Tick		

HP 2-button Optical Scroll Mouse (USB)	Dimensions (H x L x W)	1.5 x 4.5 x 2.5 in (3.8 x 11.6 x 6.3 cm)
	Weight	0.27 lb (0.12 kg)
	Cable length	72.8 in (185 cm)
	System requirements	Microsoft Windows XP, Red Hat Enterprise Linux WS 3, Red Hat Enterprise Linux WS 4

HP Optical 3-Button Mouse (USB)	Dimensions/Weight	Height	1.5 in (3.6 cm)
		Length	4.5 in (11.56 cm)

Technical Specifications – Peripherals

Environmental	Width	2.2 in (6.19 cm)
	Weight	3.80 oz (108 g)
	Operating temperature	32° to 104° F (0° to 40° C)
	Non-operating temperature	-4° to 140° F (-20° to 60° C)
Mechanical	Operating humidity	10% to 90% (non condensing at ambient)
	Tracking speed	6 in/s Maximum
	Switch life	3,000,000 operations
	Switch type	Micro-switches
	Tracking mechanism life	155 miles (250 km) at average speed of 10 in/s
	Cable length	6 ft (1.8 m)

Spaceball 5000 (USB - Windows XP Only)	Physical characteristics	Dimensions (H x W x D)	3.0 x 6.0 x 8.4 in (7.6 x 15.2 x 21.3 cm)
		Ball Diameter	2.2 in (5.6 cm)
		Weight	2.1 lb (9.94 kg)
		Features	Six degrees of freedom motion control through the X, Y, Z axis (pitch, roll, yaw) Certified for leading CAD and DCC applications
Environmental		Operating temperature	50° to 104° F (10° to 40° C)
		Non-operating temperature	43° to 140° F (6° to 60° C)
		Operating humidity	8% to 80% (non-condensing at ambient)
		Non-operating humidity	5% to 80% (non-condensing at ambient)
Mechanical		Buttons	12 programmable (unshifted)
		Ball Force Range	0.5 - 8.2N/1.8 - 29.5 oz
		Ball Torque Range	0.085 – 0.33 oz-in. (6.91 Nmm)
		Resolution	10 bits
Serial Specifications		Connector	USB 1.1 or greater
		Cable Length	12.8 ft. (3.9 m)
		Data Rate	USB model – 16 msec
		Flow Control	Xon/Xoff (on PS/2 model only)
Software Drivers Available	USB model	Microsoft Windows XP, not supported in Linux	
System Requirements	Disk Space	10 MB free disk space	
Regulatory Approvals		UL, cUL, EN 950, EN 60950, CSA, FCC, CE Mark, TUV, CISPR 22, EN 50082, IEC 1000 4-2, IEC 1000-4-3, AS/NZS, VCCI, BSMI, C-Tick	

HP SpaceMouse Plus (USB - Windows XP Only)	Physical characteristics	Dimensions (H x W x D)	7.4 x 4.72 x 1.73 in (18.8 x 12.0 x 4.4 cm)
		Cap Diameter	2 x 6.5 x 6.6 mm

Technical Specifications – Peripherals

	Weight	1.5 lb (0.68 kg)
	Features	Six degrees of freedom motion control through the X, Y, Z axis (pitch, roll, yaw) Certified for leading CAD and DCC applications
Environmental	Operating temperature	41° to 140° F (5° to 60° C)
	Non-operating temperature	-13° to 158° F (-25° to 70° C)
	Operating humidity	10 to 98 % RH (non-condensing)
	Non-operating humidity	10 to 98 % RH (non-condensing)
Mechanical	Buttons	11 programmable (unshifted)
	Cap Force Range	0.2 N – 4.5 N
	Cap Torque Range	4 Nmm to 100 Nmm
	Resolution	8 bit
USB Specifications	Connector	USB 1.1 or greater
	Cable Length	2 m
	Data Rate	16 msec
Software Drivers Available	Microsoft Windows XP, not available in Linux	
System Requirements	Disk Space	10 MB free disk space
Regulatory Approvals	UL, cUL, EN 950, EN 60950, CSA, FCC, CE Mark, TUV, CISPR 22, EN 50082, IEC 1000 4-2, IEC 1000-4-3, AS/NZS, VCCI, BSMI, C-Tick	

HP SpacePilot (USB – Windows XP Only)	Physical characteristics	Dimensions (L x W x H)	9.3" x 5.6" x 2.0" (236 x 143 x 53mm)
		Weight	1.875 lb (0.85 kg)
	Mechanical	Palmrest	Sculpted
		Buttons	21+ programmable speed keys 15 reprogrammable
		LCD Viewing Area	(W x H) 4.0" x 1.0" (102.4 x 30.2mm)
		Active Area	(W x H) 3.7" x 1.0" (93.4 x 26.2mm)
		Display Format	240x64
		Motion Controller	Six degrees of freedom motion control through the X, Y, Z axis (pitch, roll, yaw)
		Device Sensitivity	Adjustable to preference
	Connector	USB 1.1 or 2.0	
	Operating System Supported	Microsoft Windows XP, not supported in Linux	
	Regulatory Approvals	FCC, CE	

48X CD-ROM Drive	Capacity	700 MB CD disc
------------------	----------	----------------



Technical Specifications – Peripherals

Dimensions (HxWxD)	1.63 x 5.83 x 7.27 in (4.13 x 14.6 x 18.5 cm)	
Weight	1.76 lb (0.8 kg)	
Interface	ATAPI/EIDE	
Mounting Orientation	Horizontal or vertical	
Data Transfer Rates - Read	Digital audio extraction (minimum) – 1,200 KB/s (8X) CD read – up to 7,200 KB/s (48X)	
Media and Formats - Read	Formats: CD-DA, CD-ROM (Mode 1 and 2), CD-XA Ready, Photo CD (Single and Multi-session), Mixed Mode (Audio and Data combined), CD-I (FMV), CD Plus, CD-Extra; Media: stamped, CD-R, CD-RW	
Data Transfer Modes	PIO Mode 4 (16.6 MB/s); Multi-word DMA mode 2 (16.6 MB/s); UltraDMA Mode 0 (16.7 MB/s); UltraDMA Mode 2 (33.3 MB/s)	
Access Times (typical)	Random	< 75 ms @ 48x
	Full-Stroke	< 150 ms
Start-up Time (typical)	< 7 s (single session)	< 30 s (multisession)
Stop Time (typical)	< 4 s	
Read Buffer size	128 KB (minimum)	
Audio Output	Line-Out	0.7 VRMS
	Signal-to-Noise Ratio	80 dB
	Channel Separation	65 dB
Configuration Jumper Block	Master, slave, and cable select modes	
Operating Conditions	Temperature	41° to 122° F (5° to 50° C)
	Humidity	10% to 80%
Approvals/Environmental	UL 1950 (US and Canada), CSA, SEMKO, TUV; CE, FDA, FCC, IC, C-TICK	
Operating Systems Supported	Microsoft XP Professional, and XP Professional x64 Edition, Red Hat Enterprise Linux WS 3, Red Hat Enterprise Linux WS 4	
Supplied Software	None	

16X/40X DVD-ROM Drive with +R Read Support

Height	5.25-in, half-height, tray load	
Interface Type	ATAPI/EIDE	
Dimensions (W x H x D)	5.88 x 1.71 x 7.87 [max] in (149.5 x 43.25 x 200.0 [max] mm) (external, excluding bezel)	
Disc Formats	DVD-ROM (single and dual layer); DVD-video; DVD-R version 1.0 and 2.0; DVD-RW version 1.0 and 1.1; DVD-R multi-border; DVD+RW; DVD+R ; CD-ROM Mode 1 and 2; CD-DA; CD-ROM XA Mode 2, Form 1 and 2; CD-extra; CD-text; CD-I Mode 2, Form 1 and 2; CD-I ready; video CD, CD-bridge; PhotoCD (single and multi-session); CD-R; CD-RW	

Technical Specifications – Peripherals

Disc Capacity	DVD-ROM	4.7 GB (DVD-5), 8.54 GB (DVD-9), 9.4 GB (DVD-10), 3.95 GB (DVD-R version 1.0), 4.7 GB (DVD-R version 2.0), 4.7 GB (DVD-RW version 1.0 and 1.1), 4.7 GB (DVD+RW), 4.7G (DVD+R)
	CD-ROM	540 MB (Mode 1, 12 cm), 640 MB (Mode 2, 12 cm), 700 MB (80 minimum CD-R and CD-RW), 180 MB (8 cm)
Access Times (typical reads, including settling)	DVD-ROM Single Layer	120 ms
	CD-ROM Mode 1	90 ms
	Full Stroke DVD	240 ms (seek)
	Full Stroke CD	160 ms (seek)
	Startup Time	< 10 seconds (typical)
	Stop Time	< 4 seconds
	Data Transfer Modes	PIO Mode 4 (16.6 MB/s); Multi-word DMA mode 2 (16.6 MB/s); UltraDMA Mode 3 (44.4 MB/s)
Maximum Data Transfer Rates	CD-ROM Read	6000 KB/s (40X) Max
	DVD-ROM Read	21,600 KB/s (16X) Max
	Digital Audio Extraction	6000 KB/s (40X) Max
Power	Source	Four-pin, DC power receptacle
	DC Power Requirement	5 VDC \pm 5% – 100 mV ripple p-p 12 VDC \pm 5% – 200 mV ripple p-p
	DC Current	5 VDC – <800 mA typical, < 1000 mA maximum 12 VDC – < 870 mA typical, <1800 mA maximum
Audio Output	Line-Out	0.7 VRMS
	Signal-to-Noise Ratio	85 dB
	Channel Separation	65 dB
Configuration Jumper Block	Master, slave, and cable select modes	
Data Interface Connector	40-pin, shrouded and keyed, flat ribbon	
Operating Environmental (all conditions non-condensing)	Temperature (operating)	41° to 122° F (5° to 50° C)
	Relative Humidity (operating)	10% to 85%
	Maximum Wet Bulb Temperature (operating)	86° F (30° C)
Certifications, Approvals	MMC II support, multi-read certification, Microsoft WHQL certification, ACA AS/NZS 3548 class B, CNS 13438, C.I.S.P.R. Pub 22, TUV or VDE EN60950, EN 55022, EN55024, EMKO EN60950, EN 60825-1, UL 60950, CSA C22.2 60950-2000, CFR 21 part 1040 class 1, CFR 47 C.I.S.P.R. Pub 22 Class B, DHHS/FDA, ANSI C63.4-1992	

Technical Specifications – Peripherals

Operating Systems Supported	Windows XP Professional, and XP Professional x64 Edition, Red Hat Enterprise Linux WS 3, Red Hat Enterprise Linux WS 4
Kit Contents	16X/40X DVD-ROM Drive, Roxio Cineplayer Component software, audio cable, and installation guide

48X Combo CD-RW/DVD-ROM

Height	5.25-inch, half-height, tray-load
Mounting Orientation	Either horizontal or vertical
Interface Type	ATAPI/EIDE
Dimensions (W x H x D)	5.77 x 1.71 x 7.87 [max] in (14.66 x 4.34 x 20.0 [max] cm) (external, excluding bezel)
Weight (max)	2.6 lb (1.2 kg)
Read Only Disc Parameters	<p>Formats and Modes Supported</p> <p>CD-ROM-Mode 1; CD-ROM XA-Mode 2 (forms 1 and 2); CD-Bridge; CD digital audio; CD Extra; CD-I-Mode 2 (forms 1 and 2) and CD-I-Ready; Photo CD (single and multi-session); video CD; DVD (single- and double-layer); DVD-R; DVD-RW; DVD-RW Multi-Border; DVD+R; DVD+R Multisession, and DVD+RW</p> <p>Capacity</p> <p>180 MB (mode 2, 8 cm); 540 MB (mode 1, 12 cm); 650 MB (mode 2, 12 cm); 700 MB (Mode 2, 12 cm); 4.7 GB (DVD-5); 8.54 GB (DVD-9); 9.4 GB (DVD-10)</p> <p>CD-ROM, CD-R, CD-RW read</p> <p>7200 KB/s (48X) Max</p> <p>DVD ROM read</p> <p>21,632 KB/s (16X) Max</p>
Writeable Disc Parameters	<p>Disc Type</p> <p>CD-R and CD-RW</p> <p>Write Methods</p> <p>Disc at Once, Track at Once, Session at Once, Variable Packet, Fixed Packet</p> <p>Format and Modes Supported</p> <p>CD-ROM (mode 1); CD-ROM XA (mode 2, forms 1 and 2); CD digital audio, CD-I (mode 2, forms 1 and 2); video CD; CD-Bridge; Video CD</p> <p>Capacity</p> <p>180 MB (mode 2, 8 cm); 540 MB (mode 1, 12 cm); 650 MB (mode 2, 12 cm); 700 MB (mode 2, 12 cm)</p> <p>CD-R write</p> <p>7200 KB/s (48X) Max</p> <p>CD-RW write</p> <p>4800 KB/s (32X) Max</p>
Access Times (typical reads, including settling)	<p>Random DVD</p> <p>< 140 ms (typical)</p> <p>Random CD</p> <p>< 125 ms, (typical)</p> <p>Full Stroke DVD</p> <p>< 250 ms (seek)</p> <p>Full Stroke CD</p> <p>< 210 ms (seek)</p> <p>Startup Time (single)</p> <p>< 7 seconds (typical)</p> <p>Startup Time (multi-session)</p> <p>< 30 seconds (typical)</p>

Technical Specifications – Peripherals

	Stop Time	< 4 seconds
	Cache Buffer	2 MB (minimum)
	Data Transfer Modes	ATA PIO mode 4 (16.7 MB/s); ATA Multi-word DMA mode 2 (16.7 MB/s); ATA UltraDMA Mode 3 44 Mbytes/s (default)
Power	Source	Four-pin, DC power receptacle
	DC Power Requirement	5 VDC \pm 5%-100 mV ripple p-p 12 VDC \pm 5%-200 mV ripple p-p
	DC Current	5 VDC (< 1000 mA typical, < 1600 mA maximum) 12 VDC (< 600 mA typical, < 1400 mA maximum)
	Total Drive Power (standby mode)	< 2.5 Watt
Audio Output	Line-Out	0.7 VRMS
	Signal-to-Noise Ratio	74 dB
	Channel Separation	65 dB
Configuration Jumper Block	Master, slave, and cable select modes	
Data Interface Connector	40-pin, shrouded and keyed, flat ribbon	
Operating Environmental (all conditions non-condensing)	Temperature	41° to 122° F (5° to 50° C)
	Relative humidity	10% to 90%
	Maximum wet bulb temperature	86° F (30° C)
Certifications, Requirements	MPC-3 compliant, multi-read requirements, ATA Spec X3T9.2, ATAPI Spec SFF-8020, ANSI C63.4-1992, UL 1950, ACA AS/NZS 3548, CB Bulletin No. 96A, CSA C22.2 No. 950-1995, CFR 47 C.I.S.P.R. Pub 22 Class B, DHHS/FDA, EMKO-TSE 07/94, TUV EN60950, EN60825-1, MIC, BSMI-CNS 13438, CE, Microsoft PC2001 certification, Microsoft Logo for Windows XP.	
Operating Systems Supported	Windows XP Professional, and XP Professional x64 Edition, Red Hat Enterprise Linux WS 3, Red Hat Enterprise Linux WS 4	
Option Kit Contents	48X Combo CD-RW/DVD-ROM Drive, Roxio DigitalMedia Plus v7.2, Roxio Cineplayer Component, Dantz Retrospect Express 7.0, audio cable, and installation guide.	

16X DVD+/-RW LightScribe drive

Height	5.25-inch, half-height, tray-load
Orientation	Either horizontal or vertical
Interface Type	ATAPI/EIDE
Disc Recording Capacity	8.5 GB DL or 4.7 GB standard
Dimensions (W x H x D)	5.9 x 1.7 x 8.0 in (15.0 x 4.4 x 20.3 cm)
Weight (maximum)	2.6 lb (1.2 kg)

Technical Specifications – Peripherals

Write Speed (maximum)	DVD+R	Up to 16X
	DVD+RW	Up to 4X
	DVD+R DL	Up to 2.4X
	DVD-R	Up to 8X
	DVD-RW	Up to 4X
	CD-R	Up to 40X
	CD-RW	Up to 24X
Read Speed (maximum)	DVD+R/-R/+RW/-RW/+R DL	Up to 8X
	DVD-ROM	Up to 16X
	CD-ROM, CD-R	Up to 40X
	CD-RW	Up to 32X
Access Time (typical reads, including settling)	Random	DVD: < 130 ms (typical), CD: < 120 ms (typical)
	Full Stroke	DVD: < 240 ms (seek), CD: < 200 ms (seek)
	Startup Time	Single-session: < 15 seconds (typical), Multi-session: < 30 seconds (typical)
	Stop Time	< 4 seconds
	Cache Buffer	2 MB (minimum)
	Data Transfer Modes	ATA PIO mode 4 (16.7 MB/s); ATA Multi-word DMA mode 2 (16.7 MB/s); ATA UltraDMA Mode 3 (44.4 MB/s -default)
Power	Source	Four-pin, DC power receptacle
	DC Power Requirement	5 VDC \pm 5%-100 mV ripple p-p 12 VDC \pm 10%-200 mV ripple p-p
	DC Current	5 VDC (< 2000 mA typical, < 2500 mA maximum) 12 VDC (< 700 mA typical, < 2000 mA maximum)
	Total Drive Power (standby mode)	< 2.5 Watt
	Audio Output	Line-Out
	Signal-to-Noise Ratio	74 dB
	Channel Separation	65 dB
Operating Environmental (all conditions non-condensing)	Temperature	41° to 122° F (5° to 50° C)
	Relative humidity	10% to 90%
	Maximum wet bulb temperature	86° F (30° C)
System Configuration	Intel Pentium III Processor or later with 128 MB of memory (required); 256 MB recommended 2-D or 3-D graphics cards on primary disk drive for operating system and application software; second disk drive for audio and video data	

Technical Specifications – Peripherals

Operating Systems Support	Microsoft Windows XP Professional, Windows XP Home, Red Hat Enterprise Linux WS 3, Red Hat Enterprise Linux WS 4 (LightScribe functionality not supported in Linux)
Regulatory Approvals	MPC-3 compliant, multi-read requirements, ATA Spec X3T9.2, ATAPI Spec T13.1153D, ANSI C63.4-1992, UL 1950, ACA AS/NZS 3548, CB Bulletin No. 96A, CSA C22.2 No. 950-1995, CFR 47 C.I.S.P.R. Pub 22 Class B, DHHS/FDA, EMKO-TSE 07/94, TUV EN60950, EN60825-1, MIC, BSMI-CNS 13438, CE, Microsoft PC2001 certification, Microsoft Logo for Windows XP.
Option Kit contents	16X DVD+/-RW LightScribe drive, Roxio DigitalMedia Plus v7.2, Roxio MyDVD Component, Roxio Cineplayer Component, Dantz Retrospect Express 7.0, installation guide, and DVD+R media.

NVIDIA Quadro NVS 285, 128 MB Dual Head	Form Factor	Low profile, both ATX and low profile brackets included
	Graphic Controller	Integrated Quadro 285 2D graphics processor unit (GPU)
	Bus type	PCIe
	RAMDAC	Dual 350 MHz (integrated)
	Memory	128 MB DDR (64 MB local frame buffer plus 64 MB of shared system memory via TurboCache technology) NOTE: The graphics card uses part of the total system memory (RAM) for graphics performance. System memory dedicated to graphics performance is not available for other use by other programs.
	Connector	DVI DMS-59 to dual DVI Y-cable and DMS-59 to dual-VGA Y-cable
	Dimensions	Low-profile, 2.586 x 6.6 in (6.57 x 16.76 cm)
	Controller clock speed	250 MHz
	Color depth	32 bits/pixel max
	Overlay planes	One 16-bit Video overlay plane
	Maximum pixel clock	350 MHz
	Multi-monitor support	Dual analog or digital monitors
	Single DVI Support	Yes
	Dual DVI Support	Yes
	High-definition Video Processor (HDVP)	Full screen, full frame video playback of HDTV and DVD content DVD-ready motion compensation for MPEG-2 Independent hardware color controls for video overlay Hardware color-space conversion (YUV 4:2:2 and 4:2:0) IDCT motion compensation 5-tap horizontal by 3-tap vertical filtering 8:1 up/down scaling
	Available graphics drivers	Microsoft Windows XP (Provides full native Dual View mode, Span or Big Desktop mode, and Clone mode), Graphics drivers for Red Hat Enterprise Linux WS 3, and Red Hat Enterprise Linux WS 4

Technical Specifications – Peripherals

HP qualified drivers may be preloaded or available from the HP support Web site:

<http://www.hp.com/country/us/en/support.html?pageDisplay=drivers>

Analog Resolution	Maximum Colors Supported	Maximum Refresh Rate
640 x 480	16.7 M	240 Hz
800 x 600	16.7 M	240 Hz
1024 x 768	16.7 M	240 Hz
1152 x 864	16.7 M	170 Hz
1280x1024	16.7 M	150 Hz
1600 x 1200	16.7 M	100 Hz
1920 x 1080	16.7 M	85 Hz
1920 x 1200	16.7 M	85 Hz
1920 x 1440	16.7 M	75 Hz
2048 x 1536	16.7 M	60 Hz
Digital Resolution	Maximum Colors Supported	Maximum Refresh Rate
640 x 480	16.7 M	75 Hz
800 x 600	16.7 M	75 Hz
1024 x 768	16.7 M	75 Hz
1152 x 864	16.7 M	60 Hz
1280 x 1024	16.7 M	60 Hz
1600 x 1200	16.7 M	60 Hz
1900 x 1200	16.7 M	60 Hz

NVIDIA Quadro NVS 440, 256 MB Quad Head	Form Factor	ATX
	Graphic Controller	2 nv43 2D graphics processor units (GPUs)
	VGA controller	Integrated into the Quadro GPU
	Bus type	PCIe x16
	RAMDAC	Dual 350 MHz
	Memory	256 MB DDR frame buffer and Texture storage (128MB per GPU)
	Connector	Two DMS-59
	Controller clock speed	250 MHz
	Color planes	32-bit color buffer
	Overlay planes	1 16-bit Video overlay plane
	Maximum pixel clock	350 MHz
	Multi-monitor support	Up to 4 analog or digital monitors
	Single DVI Support	Yes
	Dual DVI Support	Yes

Technical Specifications – Peripherals

High-definition Video Processor (HDVP)	32-bit color 2048 x 1536 @ 60 Hz maximum resolution 2D rendering engine optimized for 32-, 24-, 16-, 15-, and 8-bpp modes
High-definition Video Processor (HDVP)	Full-screen, full-frame video playback of HDTV and DVD content DVD-ready motion compensation for MPEG-2 Independent hardware color controls for video overlay Hardware color-space conversion (YUV 4:2:2 and 4:2:0) IDCT motion compensation 5-tap horizontal by 3-tap vertical filtering 8:1 up/down scaling
Available graphics drivers	Microsoft Windows XP (Provides full native Dual View mode, Span or Big Desktop mode, and Clone mode) HP qualified drivers may be preloaded or available from the HP support Web site: http://welcome.hp.com/country/us/eng/software_drivers.html .

*NOTE: Graphics card uses "reduced blanking" timing and may not work with all panels at this resolution.

NVIDIA Quadro FX 560, 128 MB	Form Factor	ATX
	Graphics Controller	NVIDIA NV73GL
	Bus Type	PCI-Express x16
	Memory	128 MB 600 MHz GDDR3 SDRAM unified frame buffer, Z-buffer and Texture storage
	Connectors	2 DVI-I + 9-pin HDTV output
	Display resolution support	Dual integrated analog display controllers supporting up to two analog displays at 2048x1536 @ 85Hz on both displays or dual digital displays at 1920x1200 (single-link) and 3840x2400 (dual-link). NVIEW advanced multi-display desktop and application management seamlessly integrated into Microsoft® Windows®
	RAMDAC	Dual 400 MHz integrated
	Architecture features	128-bit memory interface 128-bit IEEE floating-point precision graphics pipeline 128-bit color precision 12-bit sub-pixel precision 8x FSAA at 1920x1200, 4x at 2048x1536, rotated grid FSAA sampling algorithm Hardware accelerated antialiased points and lines Hardware OpenGL overlay planes Hardware accelerated two-sided lighting Hardware accelerated clipping planes 3rd generation occlusion culling 3D volumetric texture support Quad-buffered stereo Single Link DVI enabling driving digital displays up to 1920x1200 (60Hz)

Technical Specifications – Peripherals

Shading architecture	Fully programmable GPU Long fragment programs (up to 65,536 instructions) Long vertex programs (up to 65,536 instructions) Looping and subroutines (up to 256 loops per vertex program) Dynamic flow control Conditional execution
Supported graphics APIs	OpenGL 2.0 DirectX 9.0
Available graphics drivers	Microsoft Windows XP Professional, Linux - Full Open GL implementation, complete with NVIDIA and ARB extensions. Qualified drivers may be preloaded or available from the HP support Web site: http://welcome.hp.com/country/us/eng/software_drivers.html .
Maximum Resolution	Dual DVI output – drives dual digital displays at resolutions up to 1920x1200 @ 60Hz. Internal 400MHz RAMDACs – drives dual analog displays up to 2048x1536 @ 75Hz each

ATI FireGL V3300, 128 MB	Form Factor	ATX
	Bus Type	PCI Express x16
	RAMDAC	Dual 10-bit per channel 400 MHz
	Memory	128 MB DDR unified frame buffer, Z-buffer and Texture storage
	Connectors	Dual DVI analog/digital, dual VGA analog support with DVI-to-VGA adapters.
	Display resolution support	Analog support for 2048x1536 @ 85 Hz on each output connector. Digital support for 1920x1200 @ 60 Hz on each output connector.

Additional product features

Image quality features	<ul style="list-style-type: none"> • 2x/4x/6x Anti-aliasing modes; multi-sample algorithm with gamma correction, programmable sparse sample patterns, and centroid sampling • 2x/4x/8x/16x Anisotropic Filtering modes; up to 128-tap texture filtering • High resolution texture support (up to 4K x 4K) • Hardware supported overlays, antialiased points and lines, 2 sided lighting, occlusion culling
Avivo video and display platform	<ul style="list-style-type: none"> • 64-bit per pixel floating point HDR supported throughout the pipeline, includes support for blending and multi-sample anti-aliasing • 32-bit integer HDR (10:10:10:2) format supported throughout the pipeline, includes support for blending and multi-sample anti-aliasing

Technical Specifications – Peripherals

Programmable video processor	<ul style="list-style-type: none">• Accelerated MPEG-2, MPEG-4, DivX, WMV9, VC-1 and H.264 decoding and transcoding• Seamless pixel shader integration with video in real-time
Display output	<ul style="list-style-type: none">• 16-bit per channel floating point HDR and 10 bit per channel DVI output• Programmable piecewise linear gamma correction, color correction, and color space conversion (10-bits per color)• Complete independent color controls and video overlays for each display• High quality pre- and post-scaling engines with underscan support for all outputs• Content-adaptive de-flicker filtering for interlaced displays• Spatial/temporal dithering enables 10-bit color quality on 8 and 6-bit displays• VGA mode support on all outputs
Shader Engine	<ul style="list-style-type: none">• Supports Microsoft DirectX 9.0 Shader Model 3.0 programmable vertex and pixel shaders in hardware• Full speed 128-bit floating point processing for all shader operations• Dedicated branch-execution units for high performance dynamic branching and flow control• Dedicated texture address units for improved efficiency• Up to 128 simultaneous pixel threads• Multiple Render Target (MRT) support• Render to vertex buffer support
Supported graphics APIs	OpenGL 2.0, Microsoft DirectX 9.0
Available graphics drivers	HP-tested Windows XP HP-tested Linux HP qualified drivers may be preloaded or available from the HP support web site: http://h20000.www2.hp.com/bizsupport/TechSupport/Product.jsp?prodTypeld=12454&prodCatId=296719&locale=en_US&taskId=135

NVIDIA Quadro FX 1500, 256 MB	Form Factor	ATX
	Bus Type	PCI Express x16
	Memory	256 MB 625 MHz GDDR3 SDRAM unified frame buffer, Z-buffer and Texture storage
	Connectors	2 dual-link DVI + 9-pin HDTV output

Technical Specifications – Peripherals

Display resolution support	Dual integrated analog display controllers supporting up to two analog displays at 2048x1536 @ 85Hz on both displays or dual digital displays at 1920x1200 (single-link) and 3840x2400 (dual-link). NVIEW advanced multi-display desktop and application management seamlessly integrated into Microsoft® Windows®
RAMDAC	Dual 400 MHz integrated
Architecture features	256-bit memory interface 128-bit IEEE floating-point precision graphics pipeline 128-bit color precision 12-bit sub-pixel precision 8x FSAA at 1920x1200, 4x at 2048x1536, rotated grid FSAA sampling algorithm Hardware accelerated antialiased points and lines Hardware OpenGL overlay planes Hardware accelerated two-sided lighting Hardware accelerated clipping planes 3rd generation occlusion culling 3D volumetric texture support Quad-buffered stereo Dual Link DVI enabling driving digital displays up to 3840x2400 (24Hz)
Shading architecture	Fully programmable GPU Long fragment programs (up to 65,536 instructions) Long vertex programs (up to 65,536 instructions) Looping and subroutines (up to 256 loops per vertex program) Dynamic flow control Conditional execution
Supported graphics APIs	OpenGL 2.0 DirectX 9.0
Available graphics drivers	Microsoft Windows XP Professional, Linux - Full Open GL implementation, complete with NVIDIA and ARB extensions. Qualified drivers may be preloaded or available from the HP support Web site: http://welcome.hp.com/country/us/eng/software_drivers.html .
Maximum Resolution	Dual DVI output – drives dual digital displays at resolutions up to 1920x1200 @ 60Hz (single-link) and 3840x2400 @ 24Hz (dual-link). Internal 400 MHz RAMDACs – drives dual analog displays up to 2048x1536 @ 75Hz each

ATI FireGL V7200, 256 MB	Form Factor	ATX
	Bus Type	PCI Express x16
	RAMDAC	Dual 10-bit per channel 400 MHz
	Memory	256 MB GDDR3 graphics memory with unified frame buffer, Z-buffer and Texture storage and a 512-bit Ring-Bus memory controller

Technical Specifications – Peripherals

Connectors	Dual DVI-I analog/digital, dual VGA analog support with DVI-to-VGA adapters. The DVI-I digital connectors are Dual Link capable. Stereoscopic 3D output connector with quad buffer support, HD Component Video (YPrPb) output with optional adapter.
Display resolution support	Analog support for 2048x1536 @ 85Hz on each output connector. Digital support for 1920 x1200 @ 60Hz on each output connector. Dual Link digital support for 2560 x 1600 @ 60Hz. Ideal for 30-inch widescreen displays. NOTE: Stereo supported on single display only.

Additional product features

Ring Bus memory controller	512-bit internal ring bus for highly efficient memory reads Programmable intelligent arbitration logic
Image quality features	<ul style="list-style-type: none">• 2x/4x/6x Anti-aliasing modes; multi-sample algorithm with gamma correction, programmable sparse sample patterns, and centroid sampling• 2x/4x/8x/16x Anisotropic Filtering modes; up to 128-tap texture filtering• High resolution texture support (up to 4K x 4K)• Hardware supported overlays, antialiased points and lines, 2 sided lighting, occlusion culling
Avivo video and display platform	<ul style="list-style-type: none">• 64-bit per pixel floating point HDR supported throughout the pipeline, includes support for blending and multi-sample anti-aliasing• 32-bit integer HDR (10:10:10:2) format supported throughout the pipeline, includes support for blending and multi-sample anti-aliasing
Programmable video processor	<ul style="list-style-type: none">• Accelerated MPEG-2, MPEG-4, DivX, WMV9, VC-1 and H.264 decoding and transcoding• Seamless pixel shader integration with video in real-time
Display output	16-bit per channel floating point HDR and 10 bit per channel DVI output Programmable piecewise linear gamma correction, color correction, and color space conversion (10-bits per color) Complete independent color controls and video overlays for each display High quality pre- and post-scaling engines with underscan support for all outputs Content-adaptive de-flicker filtering for interlaced displays Xilleon TV encoder for high quality analog support Spatial/temporal dithering enables 10-bit color quality on 8 and 6-bit displays VGA mode support on all outputs

Technical Specifications – Peripherals

Shader Engine	<ul style="list-style-type: none"> • Supports Microsoft DirectX 9.0 Shader Model 3.0 programmable vertex and pixel shaders in hardware • Full speed 128-bit floating point processing for all shader operations • Dedicated branch-execution units for high performance dynamic branching and flow control • Dedicated texture address units for improved efficiency • Up to 512 simultaneous pixel threads • Multiple Render Target (MRT) support • Render to vertex buffer support
Supported graphics APIs	OpenGL 2.0, Microsoft DirectX 9.0
Available graphics drivers	<p>HP-tested Windows XP</p> <p>HP-tested Linux</p> <p>HP qualified drivers may be preloaded or available from the HP support web site:</p> <p>http://h20000.www2.hp.com/bizsupport/TechSupport/Product.jsp?prodTypeId=12454&prodCatId=296719&locale=en_US&taskId=135</p>

NVIDIA Quadro FX 3500, 256 MB	Form Factor	ATX
	Bus Type	PCI Express x16
	Memory	256 MB 700 MHz GDDR3 SDRAM unified frame buffer, Z-buffer and Texture storage
	Connectors	2 dual-link DVI + 3-pin Mini DIN stereo output
	Display resolution support	Dual integrated analog display controllers supporting up to two analog displays at 2048x1536 @ 85Hz on both displays or dual digital displays at 1920x1200 (single-link) and 3840x2400 (dual-link). NVIEW advanced multi-display desktop and application management seamlessly integrated into Microsoft® Windows®
	RAMDAC	Dual 400 MHz integrated
	Architecture features	256-bit memory interface 128-bit IEEE floating-point precision graphics pipeline 128-bit color precision 12-bit sub-pixel precision 8x FSAA at 1920x1200, 4x at 2048x1536, rotated grid FSAA sampling algorithm Hardware accelerated antialiased points and lines Hardware OpenGL overlay planes Hardware accelerated two-sided lighting Hardware accelerated clipping planes 3rd generation occlusion culling 3D volumetric texture support Quad-buffered stereo Dual Link DVI enabling driving digital displays up to 3840x2400 (24Hz) SLI Link

Technical Specifications – Peripherals

Shading architecture	Fully programmable GPU Long fragment programs (up to 65,536 instructions) Long vertex programs (up to 65,536 instructions) Looping and subroutines (up to 256 loops per vertex program) Dynamic flow control Conditional execution
Supported graphics APIs	OpenGL 2.0 DirectX 9.0
Available graphics drivers	Microsoft Windows XP Professional; Linux - Full Open GL implementation, complete with NVIDIA and ARB extensions. Qualified drivers may be preloaded or available from the HP support Web site: http://welcome.hp.com/country/us/eng/software_drivers.html .
Maximum Resolution	Dual DVI-I output – drives dual digital displays at resolutions up to 1920x1200 @ 60Hz (single-link) and 3840x2400 @ 24Hz (dual-link). Internal 400MHz RAMDACs – drives dual analog displays up to 2048x1536 @ 75Hz each

Technical Specifications - Graphics

NVIDIA Quadro FX 4500, 512 MB with optional G-Sync	<p>Bus type PCI Express x16</p> <p>RAMDAC Dual 400 MHz integrated</p> <p>Memory 512 MB GDDR3 SDRAM unified graphics memory</p> <p>Connectors 2 DVH analog/digital monitor outputs, 1 3-pin Mini DIN stereo output, DVH to VGA adapters included</p> <p>Display resolution support Dual integrated display controllers supporting up to 2048x1536 @ 75Hz (analog) or 3840x2400 @ 41Hz (digital) on both displays</p>
NVIDIA Quadro FX 4500 architecture	<p>256-bit memory interface</p> <p>35.2GB/sec. memory bandwidth</p> <p>Full 128-bit floating point color precision</p> <p>12-bit subpixel precision</p> <p>65,536 fragment instruction</p> <p>65,536 vertex instruction</p> <p>3D volumetric textures</p> <p>Single-system powerwall</p> <p>12 pixels per clock rendering engine</p> <p>Hardware accelerated antialiased points & lines</p> <p>Hardware OpenGL® overlay planes</p> <p>Hardware accelerated two-sided lighting</p> <p>Hardware accelerated clipping planes</p> <p>Hardware two-sided lighting</p> <p>3rd-generation occlusion culling</p> <p>OpenGL quad-buffered stereo</p> <p>Hardware-Accelerated Pixel Read-Back</p>
Shading architecture	<p>16 textures per pixel in fragment programs</p> <p>Window ID clipping functionality</p> <p>Hardware accelerated line stippling</p> <p>Fully programmable GPU (OpenGL2.0/DirectX 9.0c class)</p> <p>Long fragment programs (up to 65,536 instructions)</p> <p>Long vertex programs (up to 65,536 instructions)</p> <p>Looping and subroutines (up to 256 loops per vertex program)</p> <p>Dynamic flow control</p> <p>Conditional execution</p>
High level shader languages	<p>Optimized compiler for Cg and Microsoft® HLSL</p> <p>OpenGL 2.0 and DirectX 9.0c support</p> <p>Open source compiler</p>
High-resolution antialiasing	<p>12-bit subpixel sampling precision enhances AA quality</p> <p>Rotated-grid full-scene antialiasing (RG FSAA)</p> <p>16x FSAA dramatically reduces visual aliasing artifacts or "jaggies" at resolution up to 1920x1200</p>
Display resolution support	<p>Dual Dual Link DVH output-drives digital displays at resolutions up to 3840 x 2400 @ 41Hz</p> <p>Internal 400 MHz DACs – Two analog displays up to 2048x1536 @ 75 Hz each</p>
nView architecture	<p>Advanced multi-display desktop & application management seamlessly integrated into Microsoft Windows®.</p>

Technical Specifications - Graphics

- Optional G-Sync** Delivers Frame lock/Genlock functionality to unprecedented levels of industrial realism, visualization and collaborative capabilities. Frame lock allows the display channels from multiple workstations to be synchronized, thus creating one large "virtual display" that can be driven by a multisystem cluster for performance scalability, while Genlock allows the graphics output to be synchronized to an external source, typically for film and broadcast video applications. The NVIDIA Quadro G-Sync requires an NVIDIA Quadro FX 4500 graphics controller and an available expansion slot.
- Supported graphics APIs** OpenGL 2.0 ICD with immediate mode support for all OGL primitive types
DirectX 9.0c
- Available graphics drivers** Microsoft Windows XP, Linux - Full Open GL implementation, complete with NVIDIA and ARB extensions.
HP qualified drivers may be preloaded or available from the HP support web site:
http://welcome.hp.com/country/us/eng/software_drivers.html

Technical Specifications - Monitors

HP L1955 Flat Panel Monitor	Panel	Type	Active matrix, thin film transistor (TFT)
		Viewable Image Area (diagonal)	19 in (48.25 cm) maximum viewable
		Screen Opening (WxH)	14.9 x 12.0 in (38.0 x 30.5 cm)
		Viewing Angle (typical)	176 degrees horizontal/176 degrees vertical (10:1 minimum contrast ratio)
		Brightness (typical)	Up to 250 nits (cd/m ²)
		Contrast Ratio (typical)	Up to 1000:1 (typical)
		Response Rate (typical)	<16 ms (typical rise + fall)
		Pixel Pitch	0.294 mm
		Color Depth Support	16.7 million colors
	Video/Other Inputs	Plug and Play	Yes (supports VESA DDC2B; PC2001 compliant)
		Self Powered USB 2.0 Hub	One upstream, four downstream ports (cable included)
		Input Signal	Two connectors: one 15-pin mini D-sub analog VGA; and one DVI-I (VGA analog or digital)
		Input Impedance	75 ohms ± 2%
		Sync Input	Separate sync (HSYNC/VSYNC); composite sync, Sync on Green (activated through on-screen display)
		Video Cable	VGA to VGA, DVI-D to DVI-D, and DVI-I to VGA
		Video Cable Length	78 in (2.0 m)
	Signal Interface/Performance	Horizontal Frequency	30 to 82 kHz
		Vertical Frequency	56 to 75 Hz
		Native Resolution	1280 x 1024 @ 75 Hz analog 1280 x 1024 @ 60 Hz digital
		Maximum Resolution (Analog)	1280 x 1024 @ 75 Hz analog
		Maximum Resolution (Digital)	1280 x 1024 @ 75 Hz digital
		Preset VESA Graphic Modes (non-interlaced)	640 x 480 @ 60 Hz, 72 Hz, 75 Hz 720 x 400 @ 70 Hz 800 x 600 @ 60 Hz, 72 Hz, 75 Hz 1024 x 768 @ 60 Hz, 70 Hz, 75 Hz 1280 x 1024 @ 60 Hz, 75 Hz
		Preset MAC Mode	832 x 624 @ 75 Hz 1152 x 870 @ 75 Hz
		Preset VGA Mode	640 x 480 @ 60 Hz, 72 Hz
		Preset SUN Mode	1152 x 900 @ 76 Hz
		Fail Safe Mode	Yes (limits out of range signal messages)

Technical Specifications - Monitors

	Maximum Pixel Clock Speed	140 MHz
	User Programmable Modes	Yes, 15
	Anti-Glare	Yes
	Anti-Static	Yes
	AssetControl	Yes (accessible on HP Compaq Business Desktops featuring Intelligent Manageability)
	Default Color Temperature	Yes (6500k, 9300k, SRGB, Custom User)
On Screen Display (OSD) Controls	Buttons or Switches	Power on/off; 3-button OSD; second level OSD buttons include dual-input switch, dedicated auto adjust switch
	Languages	English, Spanish, French, German, Italian, Japanese, Simplified Chinese
	User Controls	Size and Positioning Contrast Brightness Clock, Clock Phase Selectable Color Temperature Serial Number Mode Displayed Sleep Timer Input Selection Factory Reset Individual Color Contrast Full-screen Resolution
Power	Power Supply	Auto-ranging, 90 to 265 VAC; internal power supply
	Input Power	100 ~ 240 VAC
	Nominal Current	1.5 A maximum
	Frequency	50 ~ 60 Hz
	Average	33 watts when displaying standard office software
	Typical Power Consumption	< 40 watts
	Maximum	< 60 watts
	Power Saving	< 2 watts
	Off Mode	0 watts (when master power switch is in the off position)
	Power Cable Length	70 in (1.8 m); non-captive

Technical Specifications - Monitors

Mechanical	Dimensions (H x W x D)	Unpacked with stand	16.8 (minimum) to 22.3 (maximum) x 15.9 x 8.3 in (42.7 (minimum) to 56.6 (maximum) x 40.4 x 21.1 cm)	
		Base Area (Footprint D x W)	8.3 x 12.2 in (21.1 x 30.9 cm)	
		Panel only (without stand) (H x W x D)	13.2 x 15.9 x 3.1 in (33.5 x 40.4 x 7.9 cm)	
	Weight		Unpacked with stand	16.5 lb (7.5 kg)
			Unpacked without stand	10.5 lb (4.75 kg)
			Packaged	23.5 lb (10.7 kg)
		Bezel Width		13 mm left and right, 14 mm top, and 15 mm bottom
	Tilt Range		-5° to +35°	
	Swivel Range		± 50° horizontal swivel	
	Height Adjustable		Yes (5.1 in/13 cm adjustment range)	
	Pivot Rotation		Yes, 90 °	
	Base		Ships detached and is removable after installation	
	Environmental	Temperature – Operating		41° to 95° F (5° to 35° C)
Temperature – Non-operating			-4° to 140° F (-20° to 60° C)	
Humidity – Operating			20% to 80%	
Humidity – Non-operating			5% to 95%	
Altitude – Operating			0 to 13,000 ft (0 to 4,000 m)	
Altitude – Non-operating			0 to 40,000 ft (0 to 12,192 m)	
Options	Desktop Access Center		Features integrated microphone/headset jacks, dual function headset for phone/PC support, a MultiBay slot for adding an optical drive (sold separately), and four USB ports for easy integration of third-party digital solutions. Sold separately; part number DK985A. For more information, refer to the HP Desktop Access Center QuickSpecs.	
	HP Flat Panel Speaker Bar		Powered directly by the monitor, seamlessly attaches to the monitor's bezel to bring full multimedia support to select HP flat panel monitors. Features dual speakers with full sound range and external jack for headphones. Sold separately, part number PF804AA. For more information, refer to the HP Flat Panel Speaker Bar QuickSpecs.	

Technical Specifications - Monitors

Other	Accessories Included	VGA to VGA cable, DVI-D to DVI-D cable, DVI-I to VGA cable, USB cable, user CD-ROM with Pivot Pro software
	Software	Pivot Pro software from Portrait Displays, Inc. interacts with your PC's native graphics driver to enable seamless portrait screen redraws with a simple mouse-click or keyboard command. Pivot Pro supports 90-degree portrait and landscape views. Language support is available in English, Japanese, French, German, Spanish, Italian, and Traditional and Simplified Chinese.
	Software	HP Display LiteSaver feature lets you schedule Sleep mode at preset times to help protect the display against image retention, drastically lower power consumption and energy costs, and extend the lifespan of the monitor.
	User Guide Languages	English
	Warranty Languages	English
	Color	Carbonite, two-tone carbonite and silver (EMEA only)
	VESA Mounting	Yes (swing arm/wall mount not included); base must be removed for mounting options)
	VESA External Mounting	Yes (standard 4 hole pattern, 100 mm)
	Kensington Lock-ready	Yes
Certification and Compliance		Australian ACA Approval, Canadian Requirements/CSA, CE Marking, China CCIB/CCEE Approval, CISPR Requirements, Eastern European Approvals, Energy Star Compliant, FCC Approval, German Ergonomic (TUV and GS Mark), ISO 13406-2 Compliant (Pixel Defect Guidelines), Mexican NOM Approval, MPR-II Compliant, PC2001 Compliant, PC99 Certified, S. Korean MIC Approval, Taiwan BSMI Approval, TCO 99 or 03 depending on region (emissions, ergonomics, environment), TUV-Ergo, UL Listed, VCCI Approvals, Microsoft® Windows® Certification
Compatibility		VESA Video Signal Standard (VSI) Compliant video cards have been tested and proven compatible for use with the HP L1955 Flat Panel Monitor. Recommended for use with HP products.
Service and Warranty		Limited three-year parts and repair labor, service provider labor, and on-site service. Next Business Day advanced exchange direct replacement service available during warranty period. Certain restrictions and exclusions apply. For details, contact HP Customer Support.

HP Flat Panel Monitor LP2065	Panel	Type	20-inch Active Matrix TFT (thin film transistor)
		Viewable Image Area (diagonal)	20.1 in (51 cm)

Technical Specifications - Monitors

	Screen Opening (W x H)	16.2 x 12.17 in (41.1 x 30.9 cm)
	Viewing Angle (typical)*	Up to 178° horizontal/178° vertical (10:1 minimum contrast ratio)
	Brightness (typical)*	Up to 300 nits (cd/m ²)
	Contrast Ratio (typical)*	Up to 800:1
	Response Rate (typical)*	8 ms (gray to gray), 16 ms (rise + fall)
	Pixel Pitch	0.255 mm
	Color Depth Support	16.7 million colors
	Backlight Lamp Life (to half brightness)	45K hours
On Screen Display (OSD) Controls	Buttons or Switches	Input select, auto adjust/OSD up, OSD down, OSD menu select, power
	Languages	English, French, German, Spanish, Italian, Dutch, and Japanese
	User Controls	Brightness, contrast, positioning, color temperature, individual color control, serial number display, full screen resolutions, clock, clock phase, input selection, image control (including scaling), and factory reset
Signal Interface/ Performance	Horizontal Frequency	30 to 94 kHz (VGA input); 30 to 92 KHz (DVI input for modes with pixel clock less than 157 MHz)
	Vertical Frequency	48 to 85 Hz (VGA input); 30 to 92 KHz (DVI input for modes with pixel clock less than 157 MHz)
	Native Resolution	1600 x 1200 @ 60 Hz (recommended)
	Preset VESA Graphic Modes (non-interlaced)	1600 x 1200 @ 60 Hz, 75 Hz (VGA input) 1280 x 1024 @ 60 Hz, 75 Hz, 85 Hz 1280 x 960 @ 60 Hz 1152 x 900 @ 66 Hz 1024 x 768 @ 60 Hz, 75 Hz, 85 Hz 800 x 600 @ 60 Hz, 85 Hz 640 x 480 @ 60 Hz, 75 Hz, 85 Hz
	Text Mode	720 x 400 @ 70 Hz
	Mac Mode	1152 x 870 @ 75 Hz and 832 x 624 @ 75 Hz
	Sun Mode	1152 x 900 @ 66 Hz
	Maximum Pixel Clock Speed	202 MHz (VGA input); 162 MHz (DVI input)
	User Programmable Modes	Yes, 10
	Anti-Glare	Yes

Technical Specifications - Monitors

	Anti-Static	Yes						
	Default Color Temperature	6500 K						
Video Input	Plug and Play	Yes						
	Input Signal	Four connectors, including one 15-pin mini D-sub VGA, one DVI (VGA analog and digital input), one composite video, and one s-video						
	Self Powered USB 2.0 Hub	One upstream, four downstream ports (cable included)						
	Input Signal	Two DVI connectors (dual VGA analog or dual digital input possible)						
	Input Impedance	75 ohms \pm 10%						
	Sync Input	Separate sync (HSYNC/VSYNC); composite sync, Sync on Green						
	Video Cable	Two VGA to DVI; two DVI-D to DVI						
	Video Cable Length	5.9 ft (1.8 m)						
Power	Input Power	Auto-Ranging, 90 to 132 VAC and 195 to 265 VAC; internal power supply, 50 Hz/60 Hz						
	Frequency	47.5 to 63 Hz						
	Typical Power Consumption	55 watts (without USB ports); 70 watts (USB ports fully loaded)						
	Maximum	< 75 W						
	Power Saving	< 2 watts						
	Power Cable Length	5.9 ft (1.8 m)						
Mechanical	Dimensions (H x W x D)	<table border="0"> <tbody> <tr> <td>Unpacked with stand</td> <td>16.7 to 21.8 x 17.4 x 8.67 in (42.5 to 55.5 x 44.3 x 22.0 cm)</td> </tr> <tr> <td>Unpacked w/o stand (head only)</td> <td>13.58 x 17.4 x 3.42 in (34.5 x 44.3 x 8.7 cm)</td> </tr> <tr> <td>Packaged</td> <td>11.77 x 22.2 x 16.77 in (29.9 x 56.4 x 42.6 cm)</td> </tr> </tbody> </table>	Unpacked with stand	16.7 to 21.8 x 17.4 x 8.67 in (42.5 to 55.5 x 44.3 x 22.0 cm)	Unpacked w/o stand (head only)	13.58 x 17.4 x 3.42 in (34.5 x 44.3 x 8.7 cm)	Packaged	11.77 x 22.2 x 16.77 in (29.9 x 56.4 x 42.6 cm)
Unpacked with stand	16.7 to 21.8 x 17.4 x 8.67 in (42.5 to 55.5 x 44.3 x 22.0 cm)							
Unpacked w/o stand (head only)	13.58 x 17.4 x 3.42 in (34.5 x 44.3 x 8.7 cm)							
Packaged	11.77 x 22.2 x 16.77 in (29.9 x 56.4 x 42.6 cm)							
	Weight	<table border="0"> <tbody> <tr> <td>Unpacked</td> <td>With stand: 20.28 lb (9.2 kg); Without stand: 12.35 lb (5.6 kg)</td> </tr> <tr> <td>Packaged</td> <td>26.3 lb (11.95 kg)</td> </tr> </tbody> </table>	Unpacked	With stand: 20.28 lb (9.2 kg); Without stand: 12.35 lb (5.6 kg)	Packaged	26.3 lb (11.95 kg)		
Unpacked	With stand: 20.28 lb (9.2 kg); Without stand: 12.35 lb (5.6 kg)							
Packaged	26.3 lb (11.95 kg)							
	Tilt Range	-5° to + 25° vertical tilt						
	Swivel Range	-45° to + 45°						
	Height Adjustable	Yes, range 5.1 in (13.0 cm)						

Technical Specifications - Monitors

	Pivot Rotation	Yes
	Base	Detachable, ships attached
Environmental	Temperature – Operating	46° to 95° F (10° to 35° C)
	Temperature – Non-operating	6° to 140° F (-10° to 60° C)
	Humidity – Operating	20% to 80% non-condensing
	Humidity – Non-operating	5% to 85%
	Altitude – Operating	+12,000 ft (+3,657.6 m)
	Altitude – Non-operating	+40,000 ft (+12,192 m)
Options	HP Silver Flat Panel Speaker Bar - Part number: EE418AA	Powered directly by the monitor or the PC, the Speaker Bar seamlessly attaches to the monitor's lower bezel to bring full audio support to select HP flat panel monitors. Features include dual speakers with full sound range and external jack for headphones. Sold separately. For more information, refer to the HP Silver Flat Panel Speaker Bar QuickSpec.
	Other	
	Accessories Included	VGA to DVI-I cable - connects the graphic card's VGA connector to the monitor's input #1 or 2 (DVI-I analog) connector. DVI-D to DVI-I cable - connects the graphic card's DVI-D digital connector to the monitor's input #1 or #2 (DVI-I digital) connector.
	User Guide Languages	English, B. Portuguese, French, LA Spanish, Korean, S. Chinese, T. Chinese, Bahasa, Japanese, Danish, Finnish, German, Norwegian, Spanish, Swedish, Greek, Polish, Russian, Slovenian, Turkish
	Software	HP Display Assistant Utility makes it possible to adjust displays settings through the PC using two-way communication via DDCL. HP Display Lite Saver allows ability to power up and down display at predetermined hours of the day to save power and backlight life. Pivot Pro software from Portrait Displays, Inc. interacts with your PC's native graphics driver to enable seamless portrait screen redraws with a simple mouse-click or keyboard command. Pivot Pro supports 90-degree portrait and landscape views. Language support is available in English, Japanese, French, German, Spanish, Italian, and Traditional and Simplified Chinese.
	User Guide Languages	English
	Warranty Languages	English
	Color	Carbonite/Silver

Technical Specifications - Monitors

	VESA External Mounting	Yes (Standard 4 hole pattern, 100 mm)
	Kensington Lock-Ready	Yes
Certification and Compliance		Canadian Requirements/CSA, CE Marking, CISPR Requirements, Energy Star Compliant, FCC Approval, ISO 13406-2 Pixel Defect Guidelines, Mexican NOM Approval,, MPR-II Compliant, PC2001 Compliant, PC99 Certified, TCO 03 (emissions, ergonomics, environment), TUV-Ergo, UL Listed, VCCI Approvals, Microsoft® Windows® Certification (Microsoft® Microsoft Windows XP)
Compatibility		Compatible with platforms using the VESA standard video modes. Recommended for use with HP products.
Service and Warranty		Three years parts, labor, and on-site service. 24-hour 365-day 1-800 technical support. Replacement options include 2nd business day on-site service or next business day direct replacement. With direct replacement, HP will ship a replacement display product directly to you. Using the shipping labels provided, return your failed display to HP. Certain restrictions and exclusions apply. For details, contact HP Customer Support.

© Copyright 2006 Hewlett-Packard Development Company, L.P.

The information contained herein is subject to change without notice.

Microsoft and Windows are US registered trademarks of Microsoft Corporation. Intel and Xeon are US registered trademarks or trademarks of Intel Corporation.

The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.